## Synthesis of cuprate superconductors

C N R Rao, R Nagarajan and R Vijayaraghavan

Solid State and Structural Chemistry Unit and CSIR Centre of Excellence in Chemistry, Indian Institute of Science, Bangalore 560012, India

Received 28 August 1992, in final form 19 October 1992

Abstract. There has been unprecedented activity pertaining to the synthesis and characterization of superconducting cuprates in the last few years. A variety of synthetic strategies has been employed to prepare pure monophasic cuprates of different families with good superconducting properties. Besides the traditional ceramic method, other methods such as coprecipitation and precursor methods, the sol-gel method, the alkali flux method and the combustion method have been employed for the synthesis of cuprates. Depending on the requirements, varying conditions such as high oxygen or hydrostatic pressure and low oxygen fugacity are employed in the synthesis. In this review, we discuss the synthesis of the various types of cuprate superconductors and point out the advantages and disadvantages of the different methods. We have provided the necessary preparative details, presenting the crucial information in tabular form wherever necessary.

#### 1. Introduction

Since the discovery of high-T<sub>c</sub> superconductivity in the La-Ba-Cu-O system [1], a variety of cuprate superconductors with Tes going up to 128 K have been synthesized and characterized [2, 3]. No other class of materials has been worked on so widely and intensely in recent years as have the cuprate superconductors. Several methods of synthesis have been employed for preparing the cuprates, with the objective of obtaining pure monophasic products with good superconducting characteristics [3, 4]. The most common method of synthesis of cuprate superconductors is the traditional ceramic method which has been employed for the preparation of a large variety of oxide materials [5]. Although the ceramic method has yielded many of the cuprates with satisfactory characteristics, different synthetic strategies have become necessary in order to control factors such as the cation composition, oxygen stoichiometry, cation oxidation states and carrier concentration. Specially noteworthy amongst these methods are chemical or solution routes which permit better mixing of the constituent cations in order to reduce the diffusion distances in the solid state [5, 6]. Such methods include coprecipitation, use of precursors, the sol-gel method and the use of alkali fluxes. The combustion method or self-propagating hightemperature synthesis (sus) has also been employed. In this review, we will discuss the preparation of cuprate superconductors by the different methods, mentioning

\* Contribution No 874 from the Solid State and Structural Chemistry Unit

the special features of each method and the conditions employed for the synthesis. In table 1, we give a list of the cuprate superconductors discussed in this review along with their structural parameters and approximate  $T_c$  values. Preparative conditions such as reaction temperature, oxygen pressure, hydrostatic pressure and annealing conditions are specified in the discussion and given in tabular form where necessary. It is hoped that this review will be found useful by practitioners of the subject as well as those freshly embarking on the synthesis of these materials.

#### 2. Ceramic method

The most common method of synthesizing inorganic solids is by the reaction of the component materials at elevated temperatures. If all the components are solids, the method is called the ceramic method [5]. If one of the constituents is volatile or sensitive to the atmosphere, the reaction is carried out in sealed evacuated capsules. Platinum, silica or alumina containers are generally used for the synthesis of metal oxides. The starting materials are metal oxides, carbonates, or other salts, which are mixed, homogenized and heated at a given temperature sufficiently long for the reaction to be completed. A knowledge of the phase diagram is useful in fixing the composition and conditions in such a synthesis.

The ceramic method generally requires relatively high temperatures (up to 2300 K) which are generally attained by resistance heating. Electric are and skull techniques give temperatures up to 3300 K while highpower CO<sub>2</sub> lasers give temperatures up to 4300 K. The main disadvantages of the ceramic method are the following:

- (i) The starting mixtures are inhomogeneous at the atomic level.
- (ii) When no melt is formed during the reaction, the entire reaction has to occur in the solid state, first by a phase boundary reaction at the points of contact between the components and later by the diffusion of the constituents through the product phase. With the progress of the reaction, diffusion paths become longer and the reaction rate slower; the reaction can be speeded up to some extent by intermittent grinding between heating cycles.
- (iii) There is no simple way of monitoring the progress of the reaction. It is by trial and error that one decides on the appropriate conditions required for the completion of the reaction. Because of this difficulty, with the ceramic method one often ends up with mixtures of reactants and products. Separation of the desired products from such mixtures is difficult, if not impossible.
- (iv) Frequently it becomes difficult to obtain a compositionally homogeneous product even where the reaction proceeds nearly to completion.

Despite the above limitations, the ceramic method is widely used for the synthesis of a large variety of inorganic solids. In the case of the cuprate superconductors, the ceramic method involves mixing and grinding the component oxides, carbonates or other salts, and heating the mixture, generally in pellet form, at the desired temperature. A common variation of the method is to heat a mixture of nitrates obtained by digesting the metal oxides/carbonates in concentrated HNO<sub>3</sub> and evaporating the solution to dryness Heating is carried out in air or in an appropriate atmosphere, controlling the partial pressure of oxygen when necessary. In the case of thallium cuprates, because o the volatility and poisonous nature of the thallium oxide vapour, reactions are carried out in sealed tubes In come of the earlier preparations, the thallium cup rates were synthesized in open furnaces. This is however, not recommended. A successful synthesis by the ceramic method depends on several factors which include the nature of the starting materials (the choice of oxides, carbonates), the homogeneity of the mixture of powders, the rate of heating as well as the reaction temperature and duration.

#### 2.1. La<sub>2</sub>CuO<sub>4</sub>-related 214 cuprates

Synthesis of alkaline-earth-doped La<sub>2-x</sub>M<sub>x</sub>CuO<sub>4</sub> (M = Ca, Sr and Ba) of K<sub>2</sub>NiF<sub>4</sub> structure with superconducting transition temperatures up to 35 K is readily achieved by the ceramic method. Typically, the synthesis is carried out by reacting stoichiometric quantities of the oxides and/or carbonates around 1300 K in

and the second second

oxygen atmosphere at 0/3 A after the starting materials for the synthesis [11-13]. By starting with metal nitrates, one obtains a more homogeneous starting mixture, since the hydrated metal nitrates have low melting points leading to a uniform melt in the initial stage of the reaction. Furthermore, nitrates provide an oxidative atmosphere, which is required to obtain the necessary oxygen content.

Stoichiometric  $La_2CuO_4$  is an antiferromagnetic insulator.  $La_2CuO_4$  prepared under high oxygen pressures, however, shows superconductivity ( $T_c \sim 35 \text{ K}$ ) since the oxygen excess introduces holes just as the alkaline earth dopants [14–16].  $La_2CuO_{4+\delta}$  ( $\delta$  up to 0.05) has been synthesized by annealing  $La_2CuO_4$  under an oxygen pressure of 3 kbar at 870 K [14, 15] or 23 kbar at 1070 K [16]. Oxygen plasma has also been used to increase the oxygen content.

The next homologue of  $La_2CuO_4$  containing two Cu-O layers,  $La_{1.6}Sr_{0.4}CaCu_2O_6$  ( $T_c \sim 60$  K), has been synthesized by using high oxygen pressures [17]. The synthesis involves heating the sample at an oxygen pressure of around 20 bar at 1240 K. The material prepared at ambient oxygen pressures (in air) is an insulator. Several other high-oxygen-pressure preparations have been reported on the n=2 member of the  $La_{n+1}Cu_{2n}O_{2n+3}$  homologous series by making use of commercially available high-pressure furnaces [18, 19]. In table 2, we have summarized the preparative conditions for 214 and related cuprate superconductors.

#### 2.2. YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> and other 123 cuprates

Superconducting YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-3</sub> with the orthorhombic structure can be easily prepared by the ceramic method. Most of the investigations of the 123 compound, YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-8</sub> have been carried out on the materials prepared by reacting Y2O3 and CuO with BaCO3 [20, 21]. It is noteworthy that Rao et al [21] obtained monophasic YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> as the x = 1.0 member of the Y<sub>3-x</sub>Ba<sub>3+x</sub>Cu<sub>6</sub>O<sub>14</sub> series. In the method employed for preparing YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub>, stoichiometric quantities of high-purity Y2O3, BaCO3 and CuO are ground thoroughly and heated initially in powder form around 1223 K for a period of 24 h. Following the calcination step, the powder is ground, pelletized and sintered at the same temperature for another 24 h. Finally, annealing is carried out in an atmosphere of oxygen around 773 K for 24 h to obtain the orthorhombic YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-4</sub> phase showing 90 K superconductivity. Oxygen annealing has to be carried out below the orthorhombic tetragonal transition temperature (~960 K); tetragonal YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-8</sub> (0.6  $\leq \delta \leq$  1.0) is not superconducting. Intermittent grinding is necessary to obtain monophasic, homogeneous powders. This kind of complex heating schedule often gives rise to microscopic compositional inhomogeneities. Furthermore, CO<sub>2</sub> released from the decomposition of BaCO<sub>3</sub> can react with YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-8</sub> to form non-superconducting

the evolution of CU<sub>2</sub> d g the synthesis is to use BaO<sub>2</sub> instead of BaCO<sub>3</sub>. 23]. Some of the impurities or side products in the preparation of YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> are BaCuO<sub>2</sub>, Y<sub>2</sub>BaCuO<sub>5</sub> and Y<sub>2</sub>Cu<sub>2</sub>O<sub>5</sub> [24]. The ternary phase diagram given in figure 1 illustrates the complexites of this cuprate system.

Using BaO<sub>2</sub> as the starting material has two advantages. It has a lower decomposition temperature than BaCO<sub>3</sub> and the 123 compound is therefore formed at relatively low temperatures. BaO<sub>2</sub> acts as an internal oxygen source and the duration of annealing in an oxygen atmosphere is reduced to a considerable extent. Sharp superconducting transitions are observed in samples of YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-δ</sub> made using BaO<sub>2</sub>. Slight excess of copper in the ceramic method is reported to give cuprates with sharper transitions [25]. Preparation of YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-δ</sub> is accomplished in a shorter period if one employs metal nitrates as the starting materials [13, 23]. In table 2, we present the conditions employed for preparing 123 cuprates by the ceramic method.

Other rare-earth cuprates of the 123 type, LnBa, Cu, O, \_, where Ln = La, Nd, Sm, Eu, Gd, Dy, Ho, Er and Tm (all with T<sub>c</sub> values around 90 K) have also been prepared by the ceramic method [26, 27]. Oxygen annealing of these cuprates should also be carried out below the orthorhomic-tetragonal transition temperature [3]: La, 754 K; Nd, 837 K; Gd, 915 K; Er, 973 K; Yb, 976 K etc. Nearly 30% of Y can be substituted by Ca in YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-3</sub>, retaining the basic crystal structure [28]; the T<sub>c</sub> decreases with the increase in calcium content. Both La and Sr can be substituted at the Ba site in YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-4</sub> [29-31]. With La, monophasic products are obtained for  $0 \le x \le 1.0$ in YBa2-xLaxCu3O7-8, the Te decreasing with increase in x. In the case of Sr substitution, monophasic  $0 \le x \le 1.25$ products are obtained for YBa<sub>2-x</sub>Sr<sub>x</sub>Cu<sub>3</sub>O<sub>7-a</sub>; high  $T_c$  is retained up to x = 1.0. Ceramic methods have also been used to prepare YBa<sub>2</sub>Cu<sub>3-x</sub>M<sub>x</sub>O<sub>7-8</sub> solid solutions, where M generally stands for a transition element of the first series. In most




Figure 1. Phase diagram of the  $Y_2O_3$ -BaO-CuO system at 1220 K (from [24]).

Table 2. Preparative conditions for the synthesis of 214, 123, 124 and 247 type cuprates by the ceramic method.

|                   |  | Prepari    | Preparative conditions | \$      |                    |          |           |
|-------------------|--|------------|------------------------|---------|--------------------|----------|-----------|
| Compound          | Starting materials   | Temp. (K)  | Time                   | Gas     | Comments           | 7° (K)   | Ref       |
| La_CuO.++         | La <sub>2</sub> O <sub>3</sub> , CuO   | 1273       | 24 h                   | ë (     |                    |          |           |
|                   |  | 6/8        | - P                    | ວ໊      | 3 Kbar<br>Dressure | 35       | [15]      |
| La, Sr, (Ba,)CuO. | La203, Sr/BaCO3, CuO   | 1393       | 36 h                   | ဝ်      |                    | 40       | [10]      |
|                   | La(NO <sub>3</sub> ) <sub>3</sub> .nH <sub>2</sub> O, Sr/Ba(NO <sub>3</sub> ) <sub>2</sub> . | 1273       | 20°                    | a i     |                    | !        | ?         |
|                   | Cu(NO <sub>3</sub> ) <sub>3</sub> . nH <sub>2</sub> O  | 873        | 161                    | ဝ်      |                    | 32       | [13]      |
| La, Sro, CaCu2O   | La2C3O4. 10H2O, Sr(NO3)2.  | 1173       | 30                     | ·o      |                    | <b>!</b> |           |
|                   | Ca(NO <sub>3</sub> ) <sub>2</sub> . 4H <sub>2</sub> O, CuO                                   | 1198       | D<br>C                 | 'ô      |                    |          |           |
|                   |  | 1243       | 20                     | 'o      | 20 atm             | 9        | נויו      |
| YBa, Cu, O,       | Y2O3, BECO3, CuO   | 1223       | 20                     | air     |                    |          |           |
|                   |  | 773        | 9                      | ဝ်      |                    | 88       | [20]      |
|                   | Y2O3, B&O2, CuO  | 1198       | 2 0                    | air     |                    |          |           |
|                   |  | 723        | 70                     | ó       |                    | 88       | [22]      |
|                   | Y(NO3)3. nH3O, Ba(NO3)2.   | 1173       | 16 h                   | , E     |                    |          |           |
|                   | Cu(NO <sub>3</sub> ) <sub>3</sub> nH <sub>2</sub> O  | 1223       | £                      | ဝ်      |                    | <b>8</b> | [13]      |
| YBa,Cu,O,         | Y <sub>2</sub> O <sub>3</sub> , BaCO <sub>3</sub> , CuO                                      | 1313       | 1                      | ်<br>ဝ  | 400 bar            | 18       | [34]      |
|                   | Y <sub>2</sub> O <sub>3</sub> , Ba(NO <sub>2</sub> ) <sub>2</sub> , CuO + equal              | 1023       | <b>0</b>               | ဝ်      | 124 major phase    |          |           |
|                   | volumes of Na, CO, or K, CO,   | 1073       | 9                      | ဝ်      | + BaCuO. impurity  | 11       | [38]      |
|                   | Y303, Ba(NO3), CuO +   | 1073       | 9                      | 'ဝ်     | 124 major phase +  | 78       | [36 38]   |
|                   | 0.2M NaNO, or KNO, or Na,O,  |            |                        | •       | BaCuo. + Y.BaCuo.  |          | (an inc.) |
|                   | Y,O,, Bacuo, cuo   | 1073       | 70                     | ie<br>i | 124 major phase +  | 78       | [38]      |
|                   |  | 1088       | 5                      | ဝ်      | BaCuO, + Y.BaCuO.  | •        |           |
|                   | Y2O3, BACUO3, CUO + 0.2M NANO3 +   | 1088       | 10 d                   | o'      | 124 single phase   | 78       | [04]      |
|                   | 10 drops of dilute HNO <sub>3</sub>  |            |                        | '       |                    |          | ,         |
|                   | YBa, Cu, O, CuO  | 580<br>880 | D<br>C                 | ဝ်      | 124 major phase +  | 75       | [38]      |
|                   |  |            |                        | ,       | Bacúo.             |          |           |
| Y,Ba,Cu-O16       | Y2O2, 84CO3, CuO   | 1203       | æ                      | o"      | 19 bar             | 8        | <u>S</u>  |
|                   | Y202, Ba(NO2)2, CuO  | 1133       | <b>10</b>              | ဝ်      | Single phase       | 8        | [36]      |
|                   | Y203. Ba(NO3)2. CuO + 0.2M NaNO3   | 1133       | . <del>0</del>         | ó       | Single phase       | 8        | <u> </u>  |

\*Other rere-earth derivatives of the type LnBe<sub>2</sub>Cu<sub>3</sub>O<sub>2</sub> are also prepared by this method. Oxygen anneating is carried out below the orthorhombio-tetragonal transition temperature [26, 27].

Other rare-earth derivatives of the type LnBa<sub>2</sub>Cu<sub>2</sub>O<sub>4</sub> are obtained by a similar procedure [36, 40].

\*Other rare-earth derivatives of the type Ln<sub>2</sub>Ba<sub>4</sub>Cu<sub>2</sub>O<sub>4</sub> are prepared by a similar procedure [36, 38].

#### 2.3. YBa<sub>2</sub>Cu<sub>4</sub>O<sub>2</sub> (124), Y<sub>2</sub>Ba<sub>4</sub>Cu<sub>7</sub>O<sub>15</sub> (247) and related cuprates

The first bulk synthesis of YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> was reported by Karpinski et al [34] who heated the mixture of oxides at 1313 K, under an oxygen pressure of 400 bar. Synthesis of YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> by the conventional ceramic method without the use of high oxygen pressure suffered from some limitations due to kinetic factors. Cava et al [35] found that additives such as alkali carbonates enhance the reaction rate. The procedure involves two steps. In the first step Y2O3, Ba(NO3)2 and CuO are mixed in the stoichiometric ratio and heated at 1023 K for 16-24 h in an oxygen atmosphere. In the second step, the pre-reacted powder is ground with an approximately equal volume of either Na<sub>3</sub>CO<sub>3</sub> or K<sub>2</sub>CO<sub>3</sub> powder and pellets of the resulting mixture are heated at 1073 K in flowing oxygen for 3 days. After the reaction, the product is washed with water to remove the excess alkali carbonate and dried by gentle heating in air. The product after this step has YBa2Cu4O8 as the majority phase (T<sub>c</sub>, 77 K) with little BaCuO<sub>2</sub> impurity. Other reaction rate enhancers such as NaNO3, KNO3, dilute HNO3 and Na2O2 have also been used successfully (in small quantities) to prepare YBa2Cu4O8 [36-38]. The 124 cuprate can also be prepared without the addition of a rate enhancer by the solid state reaction of Y2O3, BaCuO2 and CuO at 1088 K in flowing oxygen [36]. Synthesis of YBa2Cu4O8 from the solid state reaction between YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> and CuO in flowing oxygen has also been reported [39]. The synthesis of YBa2Cu4O8 by the ceramic method generally takes a long time and requires repeated grinding and pelletizing.

Other rare-earth 124 cuprates, LnBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> with Ln = Eu, Gd, Dy, Ho and Er have been prepared by the ceramic method under an oxygen pressure of I atm [36, 40]. The T<sub>e</sub> of these cuprates decreases with the increasing ionic radius of the rare earth. Calcium can be substituted at the Y site up to 10% in YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub>, and the T<sub>e</sub> increases from 79 K to 87 K in such substituted YBa<sub>2</sub>Cu<sub>2</sub>O<sub>8</sub> [41]. Lanthanum can be substituted for barium in YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> [42]. Single phases of  $YBa_{2-x}La_xCu_4O_8$  have been obtained for  $0 \le x \le 0.4$ 

with the  $T_c$  decreasing with increase in x.

Extensive studies have been carried out on the synthesis of YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> under high oxygen pressures [43, 44]. The P-T phase diagram of 124, 123 and 247 cuprates is shown in figure 2. High-oxygen pressure synthesis essentially involves the solid state reaction followed by sintering under high oxygen pressures. The typical sintering temperature and the pressure at which synthesis of YBa2Cu4O8 has been carried out are 1200 K and 120 atm of oxygen (for 8 h). By the use of high oxygen pressures [45], it is possible to prepare 124 compounds with other rare earths such as Nd and Sm, which is otherwise not possible under ambient pressures.




Figure 2. Phase diagram of the 124, 247 and 123 cuprates (from [43]).

A variety of substitutions has been carried out at the Y. Ba and Cu sites in YBa, Cu, O, under high oxygen pressures. Yttrium can be substituted up to 10% by Ca in YBa, Cu, Os giving a T, of ~90 K [46]; 20% Ba has been substituted by Sr without affecting the Te [47]. Single-phase iron-substituted YBa2Cu4-xFe2O8  $(0 \le x \le 0.05)$  has been prepared at an oxygen pressure of 200 bar [48]; the Te falls monotonically with increasing iron concentration.

Bordet et al [49] first reported the preparation of Y<sub>2</sub>Ba<sub>4</sub>Cu<sub>7</sub>O<sub>15</sub> under oxygen pressures of 100-200 bar. It was soon realized that Y2Ba4Cu7O15 can be synthesized by the ceramic method under an oxygen pressure of 1 atm by a procedure similar to that employed for YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub>, except for the difference in the sintering temperature [36]. There is a narrow stability region between 1123 K and 1143 K for the 247 cuprate to be synthesized under I atm oxygen pressure. The best sintering temperature at which the 247 cuprate is formed is 1133 K. Other rare-earth 247 cuprates, Ln<sub>2</sub>Ba<sub>4</sub>Cu<sub>7</sub>O<sub>15</sub> (Ln = Dy, Er), can also be prepared by this method [36, 38]. About 5% of Y can be replaced by Ca in Y<sub>2</sub>Ba<sub>4</sub>Cu<sub>7</sub>O<sub>15</sub> and the T<sub>c</sub> increases to 94 K [42]. Substitution of La at the Ba site is limited to ~10% in Y2Ba4Cu7O15 where the Te decreases continuously with increasing lanthanum content [42].

Synthesis of 247 cuprates by the high-pressure oxygen method is generally carried out at 1203 K at an oxygen pressure of around 19 bar (for 8 h). This step is followed by slow cooling (typically 5°C min-1) to room temperature at the same pressure [50]. Other rare-earth 247 compounds, Ln<sub>2</sub>Ba<sub>4</sub>Cu<sub>7</sub>O<sub>15</sub> (Ln = Eu, Gd, Dy, Ho

and Er), have been prepared in the oxygen pressure range of 14-35 bar [50]. Preparative conditions for the 124 and 247 cuprates are given in table 2.

#### 2.4. Bismuth cuprates

Although the ceramic method is widely employed for the synthesis of superconducting bismuth cuprates of the type Bi<sub>2</sub>(Ca, Sr)<sub>n+1</sub>Cu<sub>n</sub>O<sub>2n+4+4</sub>, it is generally difficult to obtain monophasic compositions, due to various factors [51, 52]. Both thermodynamic and kinetic factors are clearly involved in determining the ease of formation as well as phasic purity of these cuprates. The n = 1 member (2201) of the formula Bi<sub>2</sub>Sr<sub>2</sub>CuO<sub>6</sub> appears to be stable around 1083 K and the n=2member, Bi<sub>2</sub>(Ca, Sr)<sub>3</sub>Cu<sub>2</sub>O<sub>8</sub> (2122) around 1113 K. The n = 3 member, Bi<sub>2</sub>(Ca, Sr)<sub>4</sub>Cu<sub>3</sub>O<sub>10</sub> (2223), can be obtained close to the melting point (1123 K) after heating for several days or even weeks. Of all the members of the Bi<sub>2</sub>(Ca, Sr)<sub>n+1</sub>Cu<sub>n</sub>O<sub>2n+4+4</sub> family, the n=2 member (2122) seems to be most stable. Bi<sub>2</sub>O<sub>3</sub>, which is often used as one of the starting materials, melts at around 1103 K. Increasing the reaction temperature therefore leads to preferential loss of volatile Bi<sub>2</sub>O<sub>3</sub>. This results in micro-inhomogeneities and the presence of the unreacted oxides in the final product. Since these materials contain so many cations, partial reaction between various pairs of oxides leading to the formation of impurity phases in the final product cannot easily be avoided. A noteworthy structural feature of all these bismuth cuprates is the presence of superlattice modulation; the modulation has nothing to do with superconductivity.

Most of the above problems have been overcome by employing the matrix reaction method [53, 54]. This method reduces the number of reacting components and gives better products. In this method, synthesis is carried out by reacting the oxide matrix made from CaCO<sub>3</sub>, SrCO<sub>3</sub> and CuO with Bi<sub>2</sub>O<sub>3</sub> in the temperature range of 1083-1123 K in air for a minimum period of 48 h. Quenching the samples in air from the sintering temperature or heating in a nitrogen atmosphere improves the superconducting properties of bismuth cuprates. The matrix reaction method yields monophasic n = 2 (2122) and n = 3 (2223) compositions showing T, values of 85 K and 110 K respectively [55, 56]. Partial melting for a short period (~5 min) also favours the rapid formation of the n = 2 (2122) and the n = 3 (2223) members.

The n=1 member,  $\mathrm{Bi_2Sr_2CuO_6}$ , showing  $T_c$  in the range 7-22 K is a rather complicated system and has two structurally different phases near the stoichiometric composition [51, 57-60]. Many workers have varied the Bi/Sr ratio and obtained single-phase materials with a  $T_c$  of 10 K at a composition which is strontium deficient,  $\mathrm{Bi_{2.1}Sr_{1.9}CuO_y}$  [60, 61]. This cuprate is best prepared by reacting the oxides and/or carbonates of the constituent metals at 1123 K in air for extended periods of time. In figure 3 we show the phase diagram of the Bi-Sr-Cu-O system. The phase diagram of the




Figure 3. Phase diagram of the Bi–Sr–Cu–O system at 1110 K in air (from [60]).

Bi<sub>2</sub>O<sub>3</sub>-SrO-CaO-CuO system at a constant Cu content is shown in figure 4.

Substitution of a small amount of lead for bismit results in good superconducting samples of n = 2 (21: and n = 3 (2223) members. A number of workers hat therefore preferred to synthesize both n = 2 (2122) a n = 3 (2223) members with substitution of lead up 25% in place of bismuth [58, 63-66]. They are obtain either by direct reaction of oxides and/or carbonates the cations or by the matrix reaction method.

Other than the matrix reaction method, melt que ching (glass route) [67, 68] and a semi-wet method [6 have been employed for the synthesis of superconducting bismuth cuprates. In the melt quenching metho the mixture of starting materials (in the form of oxid and/or carbonates) is melted in a platinum or alumin crucible around 1473 K for a short period in air arthen quenched in liquid nitrogen. The quenche specimens are given an annealing treatment around 1103 K in air to obtain the superconducting crystalling cuprates. This method has been shown to product both n = 2 (2122) and lead-doped n = 3 (2223) members




Figure 4. Section through the phase diagram of the Bi<sub>2</sub>O<sub>3</sub>—SrO–CaO–CuO system at a constant CuO content of 28.6 mol% (from [62]).

between two precursors which are precipitated separately. For example, in the preparation of Bi<sub>1.6</sub>Pb<sub>0.4</sub>Sr<sub>2</sub>Ca<sub>2</sub>Cu<sub>3</sub>O<sub>10</sub>, a precipitate of Pb, Sr and Ca (as carbonates) and one of Bi and Cu (as oxalates) are reacted at 1138 K in air for a minimum period of 72 h. The duration of the reaction for the formation of 2223 phase is drastically reduced by this method.

The starting composition of the reactant materials plays an important role in the synthesis of these cuprates. For example, strontium deficiency in the n = 1(2201) member favours monophasic compositions [59, 61]. Strontium deficiency also helps in obtaining a phase-pure n=2 (2122) member [70]. Starting with a 4:3:3:4 stoichiometry of Bi:Ca:Sr:Cu, it has been possible to obtain a monophasic 2122 member [54, 71]. The n=3 (2223) phase, on the other hand, is either obtained through the substitution of Bi by Pb (up to 25%) or by taking an excess of Ca and/or Cu [63-66, 72]. The problem of balancing between phasic purity and high T<sub>c</sub> of the cuprate gives rise to some difficulty in the synthesis of these cuprates. The coexistence of some of the members of the homologous series, especially in the form of polytypic intergrowths of different layered sequences, is also a problem. This problem is also encountered with thallium cuprates [73, 74].

The n=4 phase, Bi<sub>1.5</sub>Pb<sub>0.5</sub>Ca<sub>3</sub>Sr<sub>2</sub>Cu<sub>4</sub>O<sub>12</sub>, which was observed in an electron micrograph along with n=3 phase as an intergrowth, was synthesized in bulk by Rao et al [75] (with a small proportion of the n=3 phase) by the ceramic method. The n=4 phase has a slightly lower  $T_c$  (103 K), than the n=3 phase. This cuprate has also been prepared by Losch et al [75].

A variety of substitutions has been carried out in superconducting bismuth cuprates employing the ceramic method [58, 76-79]; some of them are noteworthy. For example, the simultaneous substitution of Bi by Pb and Sr by La in Bi<sub>2</sub>Sr<sub>2</sub>CuO<sub>6</sub> results in a modulation-free superconductor of the formula BiPbSr<sub>1+x</sub>La<sub>1-x</sub>CuO<sub>6</sub> with  $T_c$  increased to 24 K [77]. Similarly, co-substitution of Bi by Pb and Ca by Y in the n = 2 member (2122) gives a modulation-free superconductor, BiPbY<sub>0.5</sub>Ca<sub>0.5</sub>Sr<sub>2</sub>Cu<sub>2</sub>O<sub>8</sub> with a T<sub>e</sub> of 85 K [77]. Rare-earth substitution for Ca in Bi<sub>2</sub>CaSr<sub>2</sub>Cu<sub>2</sub>O<sub>8</sub> causes the Te to go up to 100 K without the introduction of the n=3 phase [58, 78]. As mentioned earlier, the n = 3 phase is stabilized by the partial substitution of lead in place of bismuth [63-65]. Another significant discovery is the iodine intercalation of the Bi-2122 superconductor [80]. Intercalation does not greatly affect the superconducting properties of the material; clearly, superconductivity is confined to the two-dimensional CuO2 sheets in these materials.

Synthesis of a new series of superconducting cuprates of the general formula  $Bi_2Sr_2(Ln_{1-x}Ce_x)_2Cu_2O_{10}$  (Bi-2222 phase with Ln = Sm, Eu, Gd) containing a fluorite-like  $(Ln_{1-x}Ce_x)_2O_2$  layer between the two  $CuO_2$  sheets has been possible by the ceramic method [81]. Partial substitution of bismuth by lead increases

sis at ou aim of  $U_2$  seem—stabilize the 2222 structure with other rare earths [8.

As mentioned earlier, one does not start with an exact stoichiometric composition to obtain the desired final product in the case of superconducting bismuth cuprates. Although structural studies (see for example [84]) indicate the presence of bismuth atoms over strontium and calcium sites as well, it is not possible to prescribe an exact initial composition to obtain the desired final stoichiometry. For example, starting from a nominal composition of (Bio, 7Pbo, 3)SrCaCu<sub>2</sub>O<sub>2</sub>, one ends up with the formation of the n = 3 (2223) member [65]. Therefore, for the purpose of characterizing the various members of the superconducting bismuth cuprates, one starts with some arbitrary composition and varies the synthetic conditions suitably to obtain the desired final product in pure form. The actual compositions of the final cuprate are quite unexpected (e.g.  $Bi_{1.83}Pb_{0.30}Sr_{2.04}Ca_{1.68}Cu_3O_p$ ) as found from analytical electron microscopy [85]. In table 3 we have summarized the preparative conditions of all the members of Bi<sub>2</sub>(Ca, Sr)<sub>n+1</sub>Cu<sub>n</sub>O<sub>2n+4+0</sub> family.

#### 2.5. Thallium cuprates

The conventional ceramic method employed for the synthesis of 214, 123 and bismuth cuprates has to be modified in the case of thallium cuprates of the  $Tl_2Ca_{n-1}Ba_2Cu_nO_{2n+4}$ ,  $TlCa_{n-1}Ba_2Cu_nO_{2n+3}$  and TICa<sub>n-1</sub>Sr<sub>2</sub>Cu<sub>n</sub>O<sub>2n+3</sub> families due to the toxicity and volatility of thallium oxide. In the early days, the reaction was carried out in an open furnace in air or oxygen atmosphere at high temperatures (1150-1180 K) for 5-10 min [86, 87]. In a typical procedure, the mixture of reactants in the form of a pellet was quickly introduced into the furnace maintained at the desired temperature. Since melt-solid reactions take place faster than solid-solid reactions, the product was formed quickly by this method [87]. Although this method requires a very short duration of heating, it results in the loss of thallium, leading to the danger of inhaling thallium oxide vapour. Some workers have taken certain precautions not to release the Tl2O3 vapour into the open laboratory, but the method is still not recommended. Furthermore, the formation of the desired phase is not ensured under the open reaction conditions. Synthesis of thallium cuprates has therefore been carried out in closed containers (sealed tubes) by most workers. By this method, both polycrystalline samples and single crystals can be prepared, since the reaction is carried out over longer periods. Better control of stoichiometry, homogeneity of phases and the total avoidance of the inhalation of toxic thallium oxide vapours are some of the advantages of carrying out sealed tube reactions.

Closed reaction conditions have been achieved in different ways. The reactant mixture is sealed in gold [88] or silver tubes [89] or in a platinum [90] or nickel





Table 3. Preparative conditions for the synthesis of bismuth cuprates by the ceramic method.

|   | Conditions* |      |                   |                    |          |
|---|-------------|------|-------------------|--------------------|----------|
| Starting composition  | Temp. (K)   | Time | Product           | T <sub>c</sub> (K) | Ref.     |
| Bi <sub>2</sub> Sr <sub>2</sub> Cu <sub>2</sub> O <sub>4</sub>                                      | 1103        | 2 d  | 2201 major phase  | 20                 | [51]     |
| Bi <sub>2</sub> Sr <sub>2</sub> CuO <sub>6</sub>  | 1123        | 1 d  | 2201 major phase  | 9                  | [57]     |
| Bi <sub>2.1</sub> Sr <sub>1.9</sub> CuO,  | 1123        | 2 d  | Single phase      | 10                 | [59, 61] |
| BiPbSr, La, CuO   | 1150        | 1 d  | Single phase      | 24                 | [דד]     |
| Bi <sub>2</sub> CaSr <sub>2</sub> Cu <sub>2</sub> O <sub>8</sub>                                    | 1103        | 5 d. | Single phase      | 85                 | [61]     |
| Bi <sub>2</sub> Ca <sub>1,5</sub> Sr <sub>1,5</sub> Cu <sub>2</sub> O <sub>8</sub> <sup>b</sup>     | 1103        | 3 d  | 2122 major phase  | 80                 | [53]     |
| Bi <sub>4</sub> Ca <sub>2</sub> Sr <sub>3</sub> Cu <sub>4</sub> O <sub>4</sub>                      | 1108        | 2 d  | 2122 single phase | 85                 | [71]     |
| Bl <sub>2</sub> Sr <sub>1,7</sub> CaCu <sub>2</sub> O <sub>4</sub>                                  | 1113        | 3 d  | 2122 single phase | 85                 | [70]     |
| BiPbSr <sub>2</sub> Y <sub>0.5</sub> Ca <sub>0.5</sub> Cu <sub>2</sub> O <sub>8</sub>               | 1200        | 1 d  | 2122 single phase | 85                 | [77]     |
| Bi, sPba CarSrrCu3O, b  | 1140        | 5 d  | 2223 major phase  | 120                | [55]     |
| Bi, 5Pbo,5Ca2,5Sr, 5Cu3O,6  | 1100        | 4 d  | 2223 major phase  | 105                | [64]     |
| Bi <sub>1.7</sub> Pb <sub>0.3</sub> Sr <sub>2</sub> Ca <sub>3</sub> Cu <sub>4</sub> O <sub>4</sub>  | 1153        | 10 d | 2223 single phase | 110                | [72]     |
| Bio.7Pbo.3SrCaCu <sub>1.8</sub> O,  | 1153        | 5 đ  | 2223 major phase  | 105                | [65]     |
| BiCaSrCu <sub>2</sub> O,  | 1143        | 5 d  | 2223 major phase  | 120                | [65]     |
| Bi <sub>3,2</sub> Pb <sub>0,0</sub> Ca <sub>5</sub> Sr <sub>4</sub> Cu <sub>7</sub> O <sub>8</sub>  | 1133        | 5 d  | 2223 major phase  | 108                | [64]     |
| Bí <sub>2</sub> Gd <sub>1,7</sub> Ce <sub>0,3</sub> Sr <sub>3</sub> Cu <sub>2</sub> O <sub>10</sub> | 1273        | 10 h | 2222 single phase | 30                 | [81]     |

<sup>\*</sup> All the preparations carried out in air.

alloy (Inconel) container [91] closed tightly with a silver lid. Alternatively, the reactant mixture is taken in the form of a pellet, wrapped in a platinum [92] or gold [93] foil and then sealed in a quartz tube. This method has the advantage of carrying out the reaction under a vacuum. Some workers place the reactant pellet in an alumina crucible [94] which is then sealed in a quartz ampoule. Thallium-excess starting compositions have been employed by a few workers to compensate for the thallium loss during the reaction [95].

In the preparation of the thallium cuprates, the matrix reaction method is often employed. Here, a mixed oxide containing all the metal ions other than the volatile thallium oxide is first prepared by reacting the corresponding oxides and/or carbonates around 1200 K for 24 h in air [89, 96]. The freshly prepared mixed oxide is then taken with a calculated quantity of Tl,O, and heated at appropriate temperatures in a scaled tube. This method is desirable when a carbonate is used as the starting material. Some of the thallium cuprates have been prepared by a modified matrix method [97] wherein a thallium-containing precursor such as Ba<sub>2</sub>Tl<sub>2</sub>O<sub>5</sub> is prepared first and then reacted with other components under closed conditions. Thalliumcontaining precursors are less volatile than Tl<sub>2</sub>O<sub>3</sub> so that the loss of thallium is minimized during the preparation.

Thermodynamic and kinetic factors associated with the synthesis of thallium cuprates are complex due to the existence of various phases which are structurally related and which can therefore intergrow with one another. In fact, one of the common defects that occurs in the thallium cuprates is the presence of random intergrowths between the various layered phases [98]. Furthermore, many of the thallium, lead and bismuth superconductors are metastable phases which are entropy stabilized [99]. The temperature of the reac-

tion, the sintering time and the starting composition are therefore all crucial to obtaining monophasic products (table 4).

The effect of the starting composition is best illustrated by the formation of the n=3 phase of the bilayer thallium cuprates (Tl<sub>2</sub>Ca<sub>2</sub>Ba<sub>2</sub>Cu<sub>3</sub>O<sub>10</sub>). Synthesis of this compound starting from the stoichiometric mixture of the oxides corresponding to the ideal composition often yields the n=2 member of the family. It was found that starting with compositions rich in Ca and/or Cu (namely TlCa<sub>3</sub>BaCu<sub>3</sub>O<sub>4</sub>, Tl<sub>2</sub>Ca<sub>4</sub>Ba<sub>2</sub>Cu<sub>5</sub>O<sub>4</sub>) yielded a nearly pure n = 3 phase [90, 98, 100]. The actual composition is, however, close to Tl<sub>1.7</sub>Ba<sub>2</sub>Ca<sub>2.3</sub>Cu<sub>3</sub>O<sub>4</sub>. In the case of TiCaBa<sub>2</sub>Cu<sub>2</sub>O<sub>2</sub> (1122) starting from a stoichiometric mixture of oxides corresponding to the ideal stoichiometry always yielded a mixture of 1122 and 2122 phases, the relative proportion of the two being dependent on the conditions. It has been demonstrated recently [101] that thallium-deficient compositions corresponding to  $Tl_{1-s}CaBa_2Cu_2O_s$  ( $\delta = 0.0$  to 0.3) yield better monophasic 1122 materials.

The thallium content of the material not only determines the number of TI-O layers but controls the hole concentration. As mentioned earlier, one of the good starting compositions to obtain  $\Pi_2\text{Ca}_2\text{Ba}_2\text{Cu}_3\text{O}_{10}$  (2223) is  $\Pi\text{Ca}_3\text{Ba}\text{Cu}_3\text{O}_1$  (1313) which bears little relation to the composition of the final product. Another example is the formation of the n=4 phase,  $\Pi\text{Ca}_3\text{Ba}_2\text{Cu}_4\text{O}_1$  (1324). Detailed studies [102] have shown that the 2223 phase formed initially transforms to the 1223 phase with an increase in the duration of heating. After prolonged sintering, the 1324 phase is formed at the expense of the 1223 phase. Similar transformations have also been observed in the formation process of  $\Pi\text{Ca}_4\text{Ba}_2\text{Cu}_3\text{O}_2$  with five Cu-O layers [103].

The Sr analogue of TlCa<sub>n-1</sub>Ba<sub>2</sub>Cu<sub>n</sub>O<sub>2n+3</sub> cannot be prepared in pure form. However, they are stabilized by

<sup>&</sup>lt;sup>b</sup> Obtained by matrix reaction method.

|   | Conditions |             |                        |                                     |                    |       |
|---|------------|-------------|------------------------|-------------------------------------|--------------------|-------|
| Starting composition  | Temp. (K)  | <b>Wime</b> | Gas                    | Product                             | T <sub>c</sub> (K) | Ref.  |
| TI <sub>2</sub> Ba <sub>2</sub> CuO <sub>8</sub>                                      | 1148       | 3 h         | Sealed gold tubes      | 2201 single phase                   | 84                 | [88]  |
| Tl <sub>2</sub> CaBa <sub>2</sub> Cu <sub>2</sub> O <sub>2</sub>                      | 1173       | 8 h         | Sealed gold tubes      | 2122 single phase                   | 98                 | [88]  |
|   | 1150       | 3 h         | Sealed silica ampoule  | 2122 single phase                   | 95                 | [98]  |
| TlaCaaBaaCuaO.  | 1150       | 0.5 h       | Sealed silica ampoule  | 2122 single phase                   | 95                 | [98]  |
| TI <sub>4</sub> Ca <sub>3</sub> Ba <sub>4</sub> Cu <sub>5</sub> O,                    | 1150       | 0.5 h       | Sealed silica ampoule  | 2122 single phase                   | 95                 | [98]  |
| Tl <sub>2</sub> Ca <sub>2</sub> Ba <sub>2</sub> Cu <sub>3</sub> O <sub>10</sub>       | 1173       | 6 h         | Sealed gold tubes      | 2223 major phase                    | 105                | [88]  |
|   | 1123       | 20 min      | Sealed silica ampoule  | 2223 major phase                    | 106                | [95]  |
|   | 1103       | 12 h        | ·                      |                                     |                    |       |
| TICa <sub>3</sub> BaCu <sub>3</sub> O,  | 1153       | 3 h         | Sealed silica ampoules | 2223 major phase                    | 125                | [100] |
| Tl <sub>2</sub> CaBa <sub>2</sub> Cu <sub>3</sub> O,                                  | 1153       | 3 h         | Sealed silica ampoules | 2223 major phase                    | 108                | [100] |
| TIBa, Lao CuOs  | 1163       | 3 h         | Sealed silica ampoules | 1021 single phase                   | 40                 | [111] |
| TISrLaCuO <sub>5</sub>  | 1170       | 2 h         | Sealed silica ampoules | 1021 single phase                   | 40                 | [109] |
| TISr2 Ndo 4CU2O   | 1170       | 2 h         | Sealed silica ampoules | 1122 major phase                    | 80                 | [110] |
| TICaBa <sub>2</sub> Cu <sub>2</sub> O <sub>7</sub>                                    | 1170       | 3 h         | Sealed silica ampoules | 1122 major phase +<br>2122 impurity | 90                 | [101] |
| TloaCaBa2Cu2O7  | 1170       | 3 h         | Sealed silver tubes    | 1122 major phase                    | 90                 | [101] |
| (TlasPbos)CaSr2Cu2O7  | 1170       | 3 h         | Sealed silica ampoules | 1122 single phase                   | 90                 | [104] |
| TI(Ca <sub>0.5</sub> Y <sub>0.5</sub> )Sr <sub>2</sub> Cu <sub>2</sub> O <sub>7</sub> | 1170       | 3 h         | Sealed silver tubes    | 1122 single phase                   | 90                 | [92]  |
| TICa <sub>2</sub> Ba <sub>2</sub> Cu <sub>3</sub> O <sub>9</sub>                      | 1163       | 6 h         | Sealed silica ampoules | 1223 single phase                   | 115                | [94]  |
| (Tlo.5Pbo.5)Ca2Sr2Cu3O9   | 1198       | 3-12 h      | Sealed gold tubes      | 1223 single phase                   | 122                | [105] |
| Tlo.sPbo.sSr <sub>4</sub> Cu <sub>3</sub> O,  | 1170       | 2 h         | Sealed silica ampoules | 1223 major phase                    | 60                 | [110] |

Conditions

partly substituting Tl by Pb (or Bi) or Ca by yttrium or a trivalent rare earth [92, 104-107]. Thus,  $Tl_{0.5}Pb_{0.5}Ca_{n-1}Sr_2Cu_nO_{2n+3}$  shows a  $T_c$  of  $\sim 90$  K for n=2 and  $\sim 120$  K for n=3.  $TlCa_{0.5}Y_{0.5}Sr_2Cu_2O_7$  also shows a  $T_c$  of 90 K. These cuprates in the Tl/Pb-Ca/Ln-Sr-Cu-O systems are prepared in a manner similar to the Tl-Ca-Ba-Cu-O system except that  $SrCO_3$  is used in place of  $BaCO_3$  or  $BaO_2$ .  $Sr_4Tl_2O_7$  has also been used as a starting material in some instances [97]. The n=1 member,  $TlM_2CuO_5$  (M = Sr or Ba) is also stabilized by the substitution of Pb or Bi for Tl or a trivalent rare earth for Sr or Ba [108-111]. All these compounds showing a  $T_c$  of 40 K have been prepared by the matrix reaction method.

Single thallium layer cuprates of the general formula  $\Pi_{1+x}A_{2-x}Ln_2Cu_2O_9$  with A=Sr, Ba; Ln=Pr (Nd, Ce) as well as  $\Pi_{0.5}Pb_{0.5}(Ln_{1-x}Ce_x)_2Sr_2Cu_2O_9$  (Ln=Pr, Gd) with a fluorite-type  $Ln_2O_2$  layer have been prepared by the ceramic method [112, 113]. The as-prepared materials are semiconductors. It has been shown by Liu et al [114] that annealing  $\Pi Ba_2(Eu, Ce)_2Cu_2O_9$  (1222 phase) under an oxygen pressure of 100 bar induces superconductivity with a  $T_c$  of ~40 K.

As in the case of bismuth cuprates, the final composition of thallium cuprates is unlikely to reflect the composition of the starting mixture. Structural studies [99, 115] have shown that there is cation disorder between Tl and Ca/Sr sites. Therefore, in order to obtain a superconducting composition corresponding to a particular copper content, one has to start with various arbitrary compositions and vary the synthesis conditions. The actual composition of the final product can be quite unexpected (e.g. Tl<sub>1.83</sub>Ba<sub>2</sub>Ca<sub>1.44</sub>Cu<sub>3</sub>O<sub>2</sub> or Tl<sub>1.86</sub>Ba<sub>2.01</sub>CuO<sub>2</sub>) as shown by analytical electron microscopy [85]. In table 4 we have listed the pre-

parative conditions employed for the synthesis of thallium cuprates by the ceramic method.

#### 2.6. Lead cuprates

The conditions for the synthesis of superconducting lead cuprates are more stringent than for the other copper oxide superconductors. Direct synthesis of members of the Pb<sub>2</sub>Sr<sub>2</sub>(Ln, Ca)Cu<sub>3</sub>O<sub>8+8</sub> (Ln = Y or rare earth) family by the reaction of the component metal oxides or carbonates in air or oxygen at temperatures below 1173 K is not possible because of the high stability of SrPbO<sub>3</sub>-related perovskite oxides. Preferential loss of the more volatile PbO leads to microinhomogeneities. Furthermore, Pb in these compounds is in the 2+ state while part of the Cu is in the 1+ state. Synthesis has therefore to be carried out under mildly reducing conditions, typically in an atmosphere of N<sub>2</sub> containing 1% O<sub>2</sub>. The most common method that has been employed for the synthesis of these lead cuprates is the matrix reaction method [116]. For  $Pb_2Sr_2(Ln, Ca)Cu_3O_{8+1}$  (Ln = Y or rare earth), a mixed oxide containing all the metal ions except Pb is made by reacting SrCO<sub>3</sub>, Ln<sub>2</sub>O<sub>3</sub> or Y<sub>2</sub>O<sub>3</sub>, CaCO<sub>3</sub> and CuO in the appropriate ratios around 1223 K in air for 16 h. The mixed oxide is then taken with an appropriate amount of PbO, ground thoroughly, pelletized and heated in the 1133-1198 K range in a flowing stream of nitrogen containing 1% O2 for periods between 1 and 16 h. Generally, short reaction times and quenching the product from the sintering temperatures into liquid nitrogen in the same atmosphere gives better-quality samples. Even though this is the common method for preparing Pb2Sr2(Ln, Ca)Cu3O8+4, it is not always easy to obtain samples exhibiting good, reproducible

superconducting properties. The lead cuprates from the method described above generally show broad transitions in the R-T curves with negative temperature coefficients of resistance above  $T_{\rm c}$ .

Studies of the dependence of T<sub>e</sub> on the calcium concentration in the Pb<sub>2</sub>Sr<sub>2</sub>Y<sub>1-x</sub>Ca<sub>x</sub>Cu<sub>3</sub>O<sub>8+6</sub> system [117] have shown that heating the samples near the melting point between 1198 and 1228 K for 2 h and postannealing in flowing nitrogen gas at a temperature between 673 and 773 K improves the superconducting properties of the samples dramatically. Direct one-step synthesis has been achieved [118] by reacting the metal oxides in sealed gold tubes around 1223 K. An alternative route to the direct synthesis from metal oxides. and/or carbonates has also been demonstrated [119]. Superconducttivity near 70 K has been reported in Ca-free  $Pb_2Sr_2LnCu_3O_{8+\delta}$  (Ln = Y or rare earth) employing the vacuum annealing procedure [120]. Substitution of Pb by Bi in Pb2Sr2Y0.5Ca0.5Cu3O8+4 has also been carried out by the ceramic method [121]. About 30% of Pb can be substituted by Bi, and such a substitution increases the  $T_c$  up to 100 K. The n=0member of the Pb2Sr2(Ca1-xLnx),Cu2+xO6+2x+4 series (namely Pb2(SrLa)Cu2O6+6) has been prepared successfully by this matrix reaction method [122].

Unlike the 2213-type lead cuprates, superconducting lead. cuprates of the formula 1212-type (Pb<sub>0.5</sub>Cu<sub>0.5</sub>)Sr<sub>2</sub>(Y<sub>0.5</sub>Ca<sub>0.5</sub>)Cu<sub>2</sub>O<sub>7-3</sub> are synthesized in an oxidizing atmosphere. Several authors have reported direct synthesis as well as reactions under closed conditions [123-127]. In the direct synthesis of these cuprates, care is taken to prevent the loss of Pb by wrapping pellets in gold or platinum foil [127]. Rouillon et al [125, 126] have reported the synthesis of 1212 lead cuprates by the direct reaction of the component oxides in evacuated silica ampoules. This method has the advantage of adjusting the oxygen partial pressure required for the synthesis. Both 2213-type and 1212-type lead cuprates have been prepared using the nitrates of the metal ions as the starting materials [128]. Although this procedure yields 2213 or 1212 phases in a single step, the product obtained always has impurities such as Y<sub>2</sub>O<sub>3</sub>, CuO etc.

A superconducting lead cuprate of the formula (Pb, Cu)(Eu, Ce)<sub>2</sub>(Sr, Eu)<sub>2</sub>Cu<sub>2</sub>O<sub>9</sub> (1222 phase) containing a fluorite layer has been prepared by the direct reaction of the component metal oxides at 1273 K in oxygen atmosphere [129].

High-pressure ceramic synthesis has been employed to prepare lead cuprates of the 1212 type [130, 131]. In order to prepare  $Pb_{0.5}Cu_{0.5}Sr_2Y_{0.5}Ca_{0.5}Cu_2O_{7-6}$ , sintering is carried out at 1213 K for 15 h under an oxygen pressure of 100 bar followed by fast cooling to 373 K. The samples obtained from high-pressure oxygen treatment show higher  $T_c$  s than those processed at 1 bar pressure of oxygen. Substitution of Y by other rare earths has been possible by this high-oxygen-pressure method [131]. All the rare-earth substituted compounds are superconducting with  $T_c$  s in the 50-70 K range. The  $T_c$  decreases with increase in the size of the rare earth. In table 5 we summarize the conditions for the synthesis of the various lead cuprates by the ceramic method.

#### 2.7 Electron-doped superconductors

All the cuprates discussed till now are hole superconductors. Synthesis of electron-doped cuprate superconductors of the type  $\text{Lin}_{2-x}M_x\text{CuO}_{4-x}$  (Ln = Nd, Pr, Sm, Eu: M = Ce, Th), possessing the T' structure, is generally achieved by the ceramic method [132-134]. The conditions of synthesis are more stringent since the

Table 5. Conditions for the synthesis of lead cuprates by the ceramic method.

|  |  | ·         | Conditio | ns                                 |  |        |       |
|--|--|-----------|----------|------------------------------------|--|--------|-------|
| Compound   | Starting materials   | Temp. (K) | Time     | G85                                | Comments   | Ta (K) | Ref.  |
| Pb <sub>2</sub> Sr <sub>2</sub> Ce <sub>0.6</sub> Y <sub>0.5</sub> Cu <sub>3</sub> O <sub>6+3</sub>                          | PbO + Sr <sub>2</sub> Y <sub>0.5</sub> Ca <sub>0.8</sub> . Cu <sub>3</sub> O <sub>4</sub> matrix   | 1143      | 1-16 h   | N <sub>2</sub> + 1% O <sub>2</sub> |  | 78     | [116] |
|  | PbO, PbO <sub>3</sub> , CaO <sub>3</sub> ,<br>SrO <sub>3</sub> , Y <sub>2</sub> O <sub>3</sub> , CuO                                     | 1223      | 12-48 h  |                                    | Sealed gold tubes  | 78     | [118] |
|  | PhO, SrCO <sub>3</sub> , Y <sub>2</sub> O <sub>3</sub> ,   | 1073      | 15 h     | air.                               |  |        |       |
|  | CaCO <sub>3</sub> , CuO  | 1173      | 2 h      | air                                |  |        |       |
|  | •  | 1073      | 1-5 h    | N <sub>2</sub>                     |  | 78     | [119] |
| Pb <sub>2</sub> Sr <sub>0.8</sub> La <sub>1.2</sub> Cu <sub>2</sub> O <sub>4+3</sub>   | PbO, La <sub>2</sub> O <sub>3</sub> ,<br>Sr <sub>2</sub> CuO <sub>3</sub> , CuO  | 1083      | 6.h      | N <sub>2</sub>                     | 2202 major phase + Pb_LaCu <sub>0.3</sub> O, Impurity                            | 26     | [122] |
| (Pbo.sCuo.s)SrLaCuO,   | PbO, SrCO, La <sub>2</sub> O <sub>3</sub> .  | 1073      | 5 h      | air                                |  |        |       |
|  | CuO  | 1273      | 2 h      | 0,                                 |  | 25     | [123] |
| (Pba, Cuo, s)Sr2   | PbO, SrCO <sub>3</sub> , Y <sub>2</sub> O <sub>3</sub> ,   | 1123      | 10 h     | air                                |  |        | _     |
| (Y <sub>0.5</sub> Ca <sub>0.5</sub> )Cu <sub>2</sub> O <sub>7.3</sub>  | CaCO <sub>3</sub> , CuO  | 1273      | 1 h      | 0,                                 | 1212 major phase +<br>Sr <sub>5</sub> Pb <sub>3</sub> CuO <sub>12</sub> Impurity | 50     | [124] |
| •  | PbO + Sr <sub>2</sub> Y <sub>0.5</sub> Ca <sub>0.5</sub><br>Cu <sub>2.3</sub> O <sub>s</sub> matrix                                      | 1243      | .3 h     | O <sub>2</sub>                     | 1212 major phase +<br>Sr <sub>p</sub> Pb <sub>3</sub> CuO <sub>12</sub> impurity | 47     | [127] |
| (Pb <sub>0.5</sub> Sr <sub>0.5</sub> )Sr <sub>2</sub><br>(Y <sub>0.5</sub> Ca <sub>0.5</sub> )Cu <sub>2</sub> O <sub>4</sub> | PbO, PbO <sub>2</sub> , Sr <sub>2</sub> CuO <sub>3</sub> ,<br>Y <sub>2</sub> O <sub>3</sub> , CaO <sub>2</sub> , Cu <sub>2</sub> O , CuO | 1108-1223 | 1–10 h   |                                    | Evacuated silica tubes   | 100    | [125] |
| (Pb <sub>0.5</sub> Ca <sub>0.5</sub> )Sr <sub>2</sub><br>(Y <sub>0.6</sub> Ca <sub>0.5</sub> )Cu <sub>2</sub> O <sub>3</sub> | PbO <sub>2</sub> , PbO, SrO <sub>2</sub> ,<br>SrCuO <sub>2</sub> , Y <sub>2</sub> O <sub>3</sub> , CaO, CuO                              | 1108-1223 | 1-10 h   |                                    | Evacuated silica tubes   | 80     | [126] |
| (Pb <sub>0.5</sub> Cu <sub>0.5</sub> )(Sr <sub>1.75</sub> Eu <sub>0.25</sub> )   | PbO, SrCO <sub>3</sub> , Eu <sub>2</sub> O <sub>3</sub> ,  | 1123      | 10 h     | air                                | Single phase   | 25     | [129] |
| (Eu, sCeo,s)Cu2O.  | CeO <sub>2</sub> , CuO   | 1323      | 1 h      | 0,                                 | 1222   |        |       |

material, by making sure that, extra electron donated by Ce4+ or Th4+ does not ease the oxygen content of the cuprate. For this reason, samples after calcination and sintering at 1323 K in air (for 24 h) are annealed in a reducing atmosphere (typically Ar, N2 or dilute H<sub>2</sub>) at 1173 K to achieve superconductivity. Samples prepared in this manner show a negative temperature coefficient of resistance above  $T_c$  in the R-Tcurves; the resistivity drop at  $T_c$  is also not sharp. An alternative synthetic route involves the reaction of pre-reacted NdCeO<sub>3,5</sub> material with the required amounts of Nd<sub>2</sub>O<sub>3</sub> and CuO at 1253 K for a minimum period of 48 h in flowing oxygen [135]. The samples are then rapidly quenched from 1253 K in an argon atmosphere to achieve superconductivity. This procedure eliminates the slow diffusion of Ce throughout the Nd<sub>2</sub>CuO<sub>4-8</sub> host and gives uniform concentrations of cerium and oxygen. Samples obtained from this route show a sharp transition at 21 K.

Superconductivity with a  $T_e$  of 25 K is induced by doping fluorine for oxygen in Nd<sub>2</sub>CuO<sub>4</sub>. This has been accomplished by taking NdF<sub>3</sub> as one of the initial reactants [136]. Substitution of either Ga or In for copper in non-superconducting Nd<sub>2-x</sub>Ce<sub>x</sub>CuO<sub>4-3</sub> also induces superconductivity [137, 138].

#### 2.8. Infinite-layer cuprates

Discovery of superconductivity in cuprates containing infinite CuO, layers has been of great importance in understanding the phenomenon. Very high pressures have been employed for obtaining the infinite-layer cuprates. Both hole-doped (e.g. Ca<sub>1-x</sub>Sr<sub>x</sub>CuO<sub>2</sub>) and electron-doped (Sr<sub>1-x</sub>Nd<sub>x</sub>CuO<sub>2</sub>) infinite-layer cuprate superconductors with a maximum T<sub>e</sub> of 110 K have been reported [139-142]. Infinite-layered cuprates of the type (Ba, Sr)CuO<sub>2</sub>, (Ca, Sr)CuO<sub>2</sub> are synthesized in an oxidizing atmosphere under high hydrostatic pressure [139, 140, 142]. Electron-doped Sr<sub>0.86</sub>Nd<sub>0.14</sub>CuO<sub>2</sub> is also prepared under high hydrostatic pressures [141]. Metal nitrates are generally used as the starting materials since carbonates of Ba, Sr and Ca have high decomposition temperatures. After decomposing the metal nitrates at around 873-1123 K in air, the product is subjected to high pressure to obtain the superconducting phases. Sr<sub>0.86</sub>Nd<sub>0.14</sub>CuO<sub>2</sub>, which superconducis at 40 K, is made under a hydrostatic pressure of 25 kbar at 1273 K. Superconducting (Ca, Sr)CuO<sub>2</sub> is prepared at 1273 K under 6 GPa pressure. Deficiency of Sr and Ca as well as the oxidizing atmosphere make this phase superconducting, and the oxidizing atmosphere is provided by heating a capsule containing KClO<sub>4</sub> along with the sample. This cuprate has a T<sub>c</sub> (onset) of 110 K.

## 3. Coprecipitation and precursor methods

Coprecipitation involves the separation of a solid containing various ionic species chemically bound to one

neous coprecipation ess can result in the formation of crystalline or amous solids. Coprecipitation of well defined stoichiometry with respect to the metal ions is obtained only when the following conditions are satisfied.

- (i) The precipitating agent is a multivalent organic compound which can coordinate with more than one metal ion, and the precipitation rate is fast.
- (ii) The solid precipitating out of the solution should be really insoluble in the mother liquor.

The anions generally preferred for coprecipitation of oxidic materials are carbonates, oxalates, citrates etc. The same is true of high- $T_{\rm c}$  cuprates. The precipitates in some instances could be genuine precursors or solid solutions [5, 6]. It is well known that precursor solid solutions drastically bring down diffusion distances for the cations and facilitate reactions in the solid state. We shall not distinguish precursor solid solutions precipitated from solutions from other precursors in this discussion.

The precipitates (carbonate, oxalate etc) are heated at appropriate temperatures in a suitable atmosphere to obtain the desired cuprate. Some of the advantages of the coprecipitation technique over the ceramic method are an homogeneous distribution of components, a decrease in the reaction temperatures and of the duration of annealing, a higher density and a lower particle size of the final product. The major drawback of this route is the control over the stoichiometry of the final product.

#### 3.1. Laz - Sr. CnO.

La, Sr and Cu in La<sub>2-x</sub>Sr<sub>x</sub>CuO<sub>4</sub> are readily coprecipitated as carbonates [11, 12, 143]. For this purpose the required quantities of the various metal nitrates are dissolved together in distilled water. Alternatively, the corresponding oxides are dissolved in nitric acid to give a nitrate solution and the pH of the solution is adjusted to 7-8 by the addition of KOH solution. A solution of K<sub>2</sub>CO<sub>3</sub> of appropriate strength is then slowly added under stirring to give a light blue precipitate which is thoroughly washed. The precipitate is dried at 420 K and calcined at 1070 K for 8 h in air. The resulting black powder is ground and pelletized and sintered at 1270 K for 16 h in air to obtain monophasic La<sub>1.83</sub>Sr<sub>0.13</sub>CuO<sub>4</sub>, superconducting at 35 K.

Instead of as carbonate, the metal ions are also readily precipitated as oxalate by the addition of either oxalic acid or potassium oxalate to the solution of metal nitrates [11, 12, 144, 145]. The precipitated oxalate is then decomposed to obtain the cuprate. This method has certain disadvantages:

(i) La<sup>3+</sup> in the presence of an alkali metal oxalate first yields lanthanum oxalate which further reacts with the precipitating agent to give a double salt. Control of stoichiometry therefore becomes difficult, leading to multiphasic products.

(ii) The relative solubilities of some of the oxalates also pose difficulties. For example,  $SrC_2O_4$  is nearly four times more soluble than  $SrCO_3$ .

#### 3.2. YBa2Cu3O7

YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> and related 123 compounds can be obtained via coprecipitation of the component metals (from a nitrate solution) as a formate [146, 147], acetate [148], oxalate [12, 149-156], hyponitrite [157] or hydroxycarbonate [158, 159]. Some of these precipitates could be genuine precursor compounds as is indeed the case with the hyponitrite.

In oxalate coprecipitation [12, 149-152], oxalic acid solution of appropriate concentration is added to an aqueous solution of mixture of nitrates of Y, Ba and Cu and the pH of the solution is adjusted to 7.5 (by dilute NH<sub>3</sub>). The pale green slurry thus formed is digested for I h, filtered and dried. The oxalate is converted to orthorhombic YBa2Cu3O2-8 by heating at 1053 K in air for 5 days followed by oxygenation at 723 K. This procedure, even though successful in making superconducting YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-8</sub> in small particulate form, often results in undesirable stoichiometry because of the moderate solubility of barium oxalate. Furthermore, rareearth ions in the presence of ammonium oxalate give a double salt with the excess oxalate which competes with the precipitation of copper and barium oxalates. These difficulties can be overcome either by taking a known excess (wt%) of barium and copper or by using triethylammonium oxalate as the precipitant in aqeuous ethanol medium [153-155]. The alcoholic medium decreases the solubility of barium oxalate and the pH of the solution is controlled in situ.

A better method of homogeneous coprecipitation of oxalates is that of Liu et al [156] using urea and oxalic acid. Urea, on heating, is hydrolysed liberating CO<sub>2</sub> and NH<sub>3</sub>, and thus gradually adjusting the pH throughout the solution. The CO<sub>2</sub> liberated controls the bumping of the solution during digestion. The oxalate coprecipitation route is widely described in the literature. The reactive powders obtained by the oxalate coprecipitation method decrease the sintering temperature. The formation of BaCO<sub>3</sub> in the intermediate calcinating step makes it difficult to obtain YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-6</sub> in pure form.

Complete avoidance of the formation of BaCO<sub>3</sub> during the synthesis is possible using the hyponitrite precursor [157]. The hyponitrite precursor is obtained from a nitrate solution of Y, Ba and Cu ions by the addition of an aqueous Na<sub>2</sub>N<sub>2</sub>O<sub>2</sub> solution. The precipitate is converted into superconducting YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-b</sub> by heating at around 973 K in an argon atmosphere, followed by oxygen annealing at 673 K. Although this route provides a convenient means of obtaining the 123 cuprate at much lower temperatures than with other methods, there is a possibility of contamination of alkali metal ions during the course of the precipitation.

YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> can also be prepared by the hydroxy-carbonate method [158, 159]. Here, KOH and K<sub>2</sub>CO<sub>3</sub>

are employed to precipitate copper as the hydroxide and Y and Ba as the carbonates in the pH range of 7-8. By employing NaOH and  $Na_2CO_3$ , complete precipitation as hydroxycarbonate is attained at a pH of  $\sim 13$ . The product from the above two procedures is homogeneous, showing sharp onset of superconductivity at 92 K. The possibility of contamination by alkali metal ions cannot, however, be avoided.

#### 3.3. YBa2Cu4O0

YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> can be prepared by the oxalate route [160] wherein the solution of Y, Ba and Cu nitrates in water is added dropwise into oxalic acid-triethylamine solution under stirring. Complete precipitation of Y, Ba and Cu with the desired stoichiometry of 1:2:4 is achieved in the pH range of 9.3-11.3. The precipitated oxalates are filtered and dried in air at 393 K. The solid obtained is then heated in the form of pellets at 1078 K in flowing oxygen for 2-4 days. The product after quenching in air shows the 124 phase as the major product with a T<sub>c</sub> of 79 K.

An alternative coprecipitation route for the synthesis of YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> is the method of Chen et al [161] in which the aqueous nitrate solution of the constituent metal ions is mixed with 8-hydroxyquinoline-triethylamine solution. The precipitated oxine is filtered, washed, dried and sintered at 1088 K in oxygen for 3 days to yield phase-pure YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> showing a T<sub>c</sub> of 80 K. Ethylenediaminetetraaceticacid [161] as well as carbonate routes [162] have also been employed for the preparation of YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub>. Coprecipitation using triethylammonium oxalate has been exploited for substituting Sr in place of Ba in YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub> [163].

#### 3.4. Bismuth cuprates

Very few coprecipitation studies have been carried out on the preparation of bismuth cuprates. One reason may be that despite the good sample homogeneity generally obtained through solution methods, the chemistry of bismuth cuprates is rather complex. It is not that easy to find compounds of all the constituent metal ions soluble in a common solvent; controlling the stoichiometry in these cuprates is also difficult in the coprecipitation procedure. Furthermore, bismuth nitrate, which is often used as one of the starting materials, decomposes in cold water to a basic nitrate precipitate as given by

$$Bi(NO_3)_3(s) \rightarrow Bi^{3+} + 3NO_3^-$$
  
 $Bi^{3+} + 3NO_3^- + 2H_2O \Rightarrow Bi(OH)_2NO_3(s) + 2H^+$ 

This problem can be overcome to some extent by preparing the nitrate solution of bismuth in nitric acid or by starting with bismuth acetate instead of the nitrate.

Bidentate ligands such as the oxalate are found to react more rapidly than multidentate ligands such as citric acid [164-174] in the coprecipitation process. Complexes of oxalic acid are also more stable than

SCELLE BOND, DATE THESE WIT the stoichiometry because of the relat, solubility of

BiC<sub>2</sub>O<sub>4</sub> or SrC<sub>2</sub>O<sub>4</sub>.

A straightforward oxalate coprecipitation is achieved by dissolving the acetates of Bi, Ca, Sr and Cu in glacial acetic acid and then adding excess oxalic acid to the solution [164]. The oxalate precipitate is dried and decomposed at around 1073 K in air and processed in the 1103-1123 K range for periods ranging from 24 h to 4 days, depending on the starting composition. The n=2 (2122) member obtained by this procedure shows zero resistance at 83 K. In another procedure reported by Zhang et al [165], first the Sr/Ca/Cu nitrate solutions are mixed in the required molar ratio. Into this solution is poured a solution of bismuth nitrate prepared in nitric acid along with oxalic acid. The complete precipitation occurs at a pH of around 5 (attained by the addition of aqueous NaOH). This process involves the possibility of contamination of sodium ions; this has been circumvented by using N(CH<sub>3</sub>)<sub>6</sub>OH to adjust the pH of the solution [166] and complete precipitation of the oxalates occurs at a pH of 12. All these procedures, however, produce mixed-phase samples.

For the preparation of the monophasic lead-doped n=3 member (2223), oxalate coprecipitation has been found effective [167-174]. In the procedure reported by Chiang et al [171], the molar ratio of the chelating agent (oxalic acid) and the nitrate anions (from the metal nitrate solutions) is fixed at 0.5 and the pH, adjusted by NH4OH solution, at which complete precipitation occurs is 6.7. The product from this method, Bi1,4Pb0.6Sr2Ca2Cu3O,, after sintering at 1133 K in air

for 72 h, shows a T, of 110 K.

Coprecipitation as oxalates to prepare the leaddoped n = 3 member (2223) has been achieved from an ethylene glycol medium using triethylammonium oxalate and oxalic acid [172]. A more easily controlled and reproducible oxalate coprecipitation procedure appears to be that of Shei et al [173] where in a mixture of triethylamine and oxalic acid is employed. The advantage of using triethylamine is that it has a higher basicity and a lower complexing ability towards Cu(II) than has ammonia. Control of the stoichiometry of the final product is therefore better obtained with this procedure; precipitation occurs in the pH range 1.5-2.2. The coprecipitated oxalates sintered at 1133 K in air for a minimum period of 72 h give monophasic Bi<sub>1:4</sub>Pb<sub>0.6</sub>Sr<sub>2</sub>Ca<sub>2</sub>Cu<sub>3</sub>O<sub>10</sub> with a T<sub>e</sub> of 110 K. It is possible to avoid adjusting the pH in the coprecipitation of oxalates [174]. The procedure involves coprecipitating the oxalates from dilute acetate solutions instead of from nitrate solutions. The oxalates are then converted to nearly phase-pure Bi<sub>1.6</sub>Pb<sub>0.4</sub>Sr<sub>2</sub>Ca<sub>2</sub>Cu<sub>3</sub>O<sub>10</sub> (T<sub>e</sub> of 106 K) by sintering at 1123 K in air for 160 h.

Carbonate corprecipitation has also been carried out for the synthesis of superconducting bismuth cuprates [175, 176], but the method does not yield monophasic products.


Coprecipitation of the m-pased cuptaies from aqueous solutions as oximates is bindered by the solubility of thallium oxalate. However, Bernhard and Gritzner [177] have found that complete coprecipitation as oxalates can be achieved by starting with thallium acetate in glacial acetic acid medium. In the procedure reported for the preparation of the n=3member (2223), stoichiometric amounts of thallium acetate, CaCO<sub>3</sub>, BaCO<sub>3</sub> and copper acetate are dissolved in water containing glacial acetic acid. The solution containing all the cations is then added to a solution of oxalic acid (excess) under stirring. The precipitate, after digestion for 1 h, is filtered, washed and dried. The oxalates are heated in the form of pellets (wrapped in gold foil) at around 1173 K for 6 min in an oxygen atmosphere. The product after annealing in the same atmosphere shows 2223 as the major phase with a T. of 118 K.

#### 3.6. Lead cuprates

Carbonate coprecipitation is found to be satisfactory for the synthesis of representative members of superconducting lead cuprates [128] of 2213 and 1212 Pb2Sr2Y0.5Ca0.5Cu3O0+0 namely Pb<sub>0.5</sub>Sr<sub>0.5</sub>Sr<sub>2</sub>Y<sub>0.5</sub>Ca<sub>0.5</sub>Cu<sub>2</sub>O<sub>7-8</sub>. Coprecipitation carbonates has been achieved by adding the nitrate solution of the constituent metal ions to an aqueous solution of sodium carbonate (in excess) under constant stirring. The carbonate precipitate thus obtained is washed and dried. The decomposed powder is heated in the form of pellets around 1153 K in a suitable atmosphere. Pb2Sr2Ca0.5Y0.5Cu3O8+0 obtained by this method after heating for 4 h in nitrogen containing 1%  $O_2$  showed 2213 as the major phase ( $T_c \sim 74$  K) with impurities such as Y2O3, CuO. The 1212 phase obtained after heating in oxygen at 1153 K for 12 h showed a broad transition with a T<sub>c</sub> (onset) of 100 K. This method has the advantage of single heating rather than the multistep procedures required in the other methods.

#### 4. Sol-gel process

The sol-gel process is employed in order to get homogeneous mixing of cations on an atomic scale so that the solid state reaction occurs to completion in a short time and at the lowest possible temperature. The term sol often refers to a suspension or dispersion of discrete colloidal particles, while a gel represents a colloidal or polymeric solid containing a fluid component which has the internal network structure wherein both the solid and the fluid components are highly dispersed. In the sol-gel process a concentrated sol of the reactant oxides or hydroxides is converted to a semi-rigid gel by removing the solvent. The dry gel is heated at an appropriate



Two different routes for the sol-gel process are usually described in the literature for the synthesis of high-T<sub>c</sub> cuprate superconductors:

(i) Via molecular precursors (e.g. metal alkoxides) in organic medium;

(ii) Via ionic precursors in aqueous medium (citrate gel process).

The purity, microstructure and physical properties of the product are controlled by varying the precursor, solvent, pH, firing temperatures and atmosphere of heat treatment.

#### 4.1. 214 Cuprates


Superconducting 214 compounds are prepared both by means of organometallic precursor [178] and by the citrate gel process [11]. Lanthanum 2,4-pentane dionate, barium 2,4-pentane dionate and copper (II) ethyl hexanoate are mixed at room temperature in the appropriate ratios in methoxyethanol medium to obtain the organometallic precursor. After vigorous stirring at room temperature, the precursor gel is converted to monophasic La<sub>1.9</sub>Ba<sub>0.1</sub>CuO<sub>0</sub> (T<sub>c</sub> 23 K) by firing at 873 K in oxygen.

In the citrate gel process, a mixture of citric acid and ethylene glycol is added to the solution containing the required quantities of metal nitrates. The resulting solution is vigorously stirred and heated around 393 K. During this process, oxides of nitrogen evolve, resulting in a viscous gel. The gel is decomposed at 673 K in air and the resulting black powder is then given the necessary heat treatment to obtain the superconducting oxide.

#### 42 YBO, CO, O,

In the case of YBa, Cu, O, -4, the alkoxide precursors are both very expensive and difficult to obtain. In addition, the solubility of copper alkoxides is very low in organic solvents and yttrium alkoxides are readily hydrolysed even by a trace of water. Despite these difficulties, superconducting YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-2</sub> has been prepared using alkoxides [157, 179-181]. A simple reaction involving Y(OCHMe2)3, Ba(OCHMe2)2 and Cu(NBu2) in THF in an argon atmosphere gives the organometallic precursor [157]. The precursor powder, after removal of the solvent, is sintered at 973 K in flowing argon to obtain tetragonal YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-4</sub>. Following oxygenation at 673 K, the product shows a  $T_c$  of 85 K. Superconducting properties have been improved by using n-butoxides of Y, Ba and Cu in butanol solvent [179].

Alternatively, methoxyethoxides of yttrium, barium and copper have been used as precursors in methoxyethanol-methylethylketone-toluene solvent mixture to prepare YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-8</sub> [180]. In some of the preparations, Cu(NO<sub>3</sub>)<sub>2</sub> (soluble in ethanol) or copper



Modified sol-gel methods which do not involve the metal alkoxide precursors have been employed by many workers. Thus, Nagano and Greenblatt [185] have employed metal nitrates dissolved in ethylene glycol. After refluxing around 353 K under vigorous stirring, a bluish green colloidal gel is obtained. The gel is converted into orthorhombic YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-1</sub>, by heating to 1223 K in flowing oxygen. Precipitating all the three ions as hydroxides also results in fine colloidal particles of the starting materials [186-188]. The precipitation is generally carried out by the addition of NH<sub>4</sub>OH [186], N(CH<sub>3</sub>)<sub>4</sub>OH [187] or Ba(OH)<sub>2</sub> [188] to a solution of metal nitrates (pH range 7-8). These hydroxides are decomposed around 1223 K in oxygen to give YBa<sub>2</sub>Cu<sub>3</sub>O<sub>2</sub> showing a T<sub>6</sub> of 93 K.

YBa2Cu3O7-0 has been prepared by the citrate gel process [189-193]. In this method 1 g equivalent of citric acid is added to each gram equivalent of the metal. The pH of the solution is adjusted to around 6 (either by NH<sub>o</sub>OH or by ethylenediamine). Evaporation of the solvent (water) around 353 K, results in a viscous dark blue gel. The gel is decomposed and the powder sintered in the form of pellets at 1173 K in oxygen to obtain orthorhombic YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7- $\delta$ </sub> ( $T_c = 93$  K). By this method, ultrafine homogeneous powders (particle size  $\sim 0.3 \mu m$ ) are obtained. The crucial step in this process is the adjustment of the pH which controls the stoichiometry of the final product. This limitation has been overcome by dispersing the citrate metal ion complexes in a solvent mixture of ethylene glycol and water [194, 195].

Problems such as the formation of BaCO<sub>3</sub> during the calcination step, filtration and contamination of alkali metal ions in the final product are avoided in the sol-gel process. Furthermore, perfect homogeneity is obtained before calcination. The sol-gel process (e.g. citrate process) has the advantage over the other methods in that the gel can be used for making thick and thin superconducting films, fibres etc which have technological importance [179, 185, 186, 196-198].

#### 43. YBo2Cm4O0

The sol-gel method offers a good alternative to the ceramic method for the synthesis of superconducting  $YBa_2Cu_4O_8$ . The following procedure has been used to prepare  $YBa_2Cu_4O_0$  at 1 atm oxygen pressure [199]. Appropriate quantities of  $Y(n - OC_4H_9)_3$ ,  $Ba(s - OC_4H_9)_2$  and  $Cu(s - OBu)_2$  in butanol-xylene mixture are refluxed in an argon atmosphere at 343 K for a period of 30 h. The fine powder after the vigorous reaction is freed from the solvent and dried. The powder is heated in the form of pellets at 1033 K in flowing oxygen to obtain superconducting  $YBa_2Cu_4O_8$ ,

used as the source of copper in this pro re [200].

In the modified citrate gel process to prepare  $YBa_2Cu_4O_8$  [201, 202], I g equivalent of citric acid is added for each gram equivalent of the metal and the pH of the solution is adjusted to ~5.5 by the addition of ethylenediamine. The resulting clear solution is evaporated to yield a viscous purple gel. The decomposed gel is sintered in flowing oxygen for 3-5 days at 1088 K to obtain nearly monophasic  $YBa_2Cu_4O_8$  ( $T_c = 66$  K). Kakihana et al [203] have reported the preparation of  $YBa_2Cu_4O_8$  using a precursor obtained from citrate metal ion complexes uniformly dispersed in a solvent mixture of ethylene glycol and water. This method yields phase-pure  $YBa_2Cu_4O_8$  ( $T_c \sim 79$  K) and eliminates the need to adjust the pH.

#### 4.4. Bismuth cuprates

There have been very few reports of the preparation of bismuth-based cuprate superconductors by the alkoxy sol-gel method [204]. Some of the difficulties arise because the relevant bismuth/lead alkoxides are not readily available; it is also not easy to get a common organic solvent to dissolve the various metal alkoxides simultaneously. Dhalle et al [204] have, however, attempted to synthesize the lead-doped n = 3 member (2223) using organometallic precursors involving propionates. The starting materials were taken in the form of nitrates and converted into propionates by the addition of an excess of 100% propyl alcohol. This step was followed by the addition of ammonium hydroxide and ethylene glycol to increase the alkoxy anion concentration, thus in turn increasing the viscosity of the solution. All the solutions were mixed together and dried at 353 K. The resin after calcination at 1123 K in air and sintering at 1118 K gave a mixture of the n=3 and n=2members.

A simple sol-gel method involving the addition of dilute ammonia to an aqueous solution containing nitrates of Bi, Sr and acetates of Ca, Cu and Pb (until the pH of the solution reached around 5.5) has also been employed to prepare bismuth cuprates [205, 206]. The blue solution after concentrating at around 343 K gives a viscous gel. The gel is decomposed and the powder sintered at around 1128 K in air. The product from this procedure is multiphasic showing a  $T_c$  of 104 K. The simplicity of the method and the formation of the n=3 phase in a short time makes it somewhat superior to the conventional ceramic route. The modified citrate gel process has been employed to prepare the n=2 member (2212) in pure form with a  $T_c$  of 78 K [193].

#### 4.5. Lead cuprates

The modified citrate gel process has been successfully employed by Mahesh et al [207] for the synthesis of lead cuprates of the 2213 or 1212 type. In a typical procedure, a mixture of citric acid and ethylene glycol in

is concentrated at 373 is order to get a viscous gel. The gel after decomposition is heated in the form of pellets in the temperature range of 1073-1173 K either in N<sub>2</sub> containing 1% O<sub>2</sub> or in an oxygen atmosphere. Pb<sub>2</sub>Sr<sub>2</sub>Y<sub>0.5</sub>Ca<sub>0.5</sub>Cu<sub>3</sub>O<sub>8+0</sub> obtained from this process shows a sharp superconducting transition at 70 K. The 1212 cuprate also shows a sharp transition at 60 K. This process is superior to the ceramic procedure for synthesizing superconducting lead cuprates.

#### 5. Amaii flun method

Strong alkaline media, either in the form of solid carbonate fluxes, molten hydroxides or highly concentrated alkali solutions can be employed for the synthesis of high-T<sub>c</sub> cuprate superconductors. The alkali flux method takes advantage of both the moderate temperatures of the molten media (453-673 K) as well as of the acid-base characteristics of molten hydroxides to simultaneously precipitate oxides or oxide precursors such as hydroxides or peroxides of the constituent metals. The method stabilizes higher oxidation states of the metal by providing an oxidizing atmosphere.

Employing fused alkali hydroxides, Ham et al [208] have synthesized superconducting La2-xMxCuO4 (M = K or Na or vacancy) at relatively low temperatures (470-570 K). In this method, stoichiometric quantities of La2O3 and CuO are added to a molten mixture containing KOH and NaOH (in an approximately 1:1 ratio) in a Teflon crucible and heated at around 570 K in air for 100 h. The 1:1 mixture of KOH and NaOH melts at 440 K and since the alkali hydroxides generally contain some water, the melt is acidic and can readily dissolve oxides such as La2O3 and CuO. The black crystals obtained from the reaction (after washing away the excess hydroxide with water) show a  $T_c$  of 35 K. Since the reaction is carried out in alkali hydroxides, incorporation of Na+ or K+ ions for La3+ in the lattice of La2CuO4 cannot be ruled out. It should be noted that superconducting alkali-doped La2CuO4 is normally prepared at higher temperatures in sealed gold tubes [209]. Recently, alkaline hypobromite oxidation has been employed to obtain La2CuOa+s with a Te of 44 K [210].

Superconducting YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> ( $T_e \sim 88$  K) has also been prepared using the fused eutectic of sodium and potassium hydroxides in a similar manner to that described above [211]. The problem of contamination of alkali metals in the preparation of YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> has been overcome by using the Ba(OH)<sub>2</sub> flux [211]. The procedure involves heating a mixture containing stoichiometric amounts of Y(NO<sub>3</sub>)<sub>3</sub>.6H<sub>2</sub>O, Ba(OH)<sub>2</sub> and Cu(NO<sub>3</sub>)<sub>2</sub>.3H<sub>2</sub>O in an open ceramic crucible at around 1023 K in air for a short time (about 10 min) and then slowly cooling the melt to room temperature. Since Ba(OH)<sub>2</sub> has two hydration states, one melting at 351 K and the other at 681 K, the lower-melting hydrate acts as the solvent for the nitrates of copper

and yttrium while the high-melting hydrate serves as the medium for intimate mixing of the reactants. The precipitate obtained from the melt, after washing with water, is sintered in air at around 1173 K followed by oxygenation at 773 K. This method yields an orthorhombic YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> phase (with little CuO impurity) showing a T<sub>c</sub> of 92 K.

The flux method eliminates the need for mechanical grinding and introduction of carbon-containing anions, which is often encountered in the solution routes. Furthermore, the method is efficient and cost-effective.

#### 6. Combustion method

Although many of the solution routes discussed earlier yield homogeneous products, the processes involved are quite complex. Combustion synthesis or self-propagating high-temperature synthesis (SHS), first developed by Merzhanov and Borovinskaya [212], provides a simple and rapid means of preparing inorganic materials, many of which are technologically important. Combustion synthesis is based on the principle that the heat energy liberated by many exothermic non-catalytic solid-solid or solid-gas reactions can self-propagate throughout the sample at a certain rate. This process can therefore occur in a narrow zone which separates the starting substances and reaction products.

Self-propagating combustion has been employed recently in this laboratory to synthesize members of almost all families of cuprate superconductors (except for the thallium cuprates) [213]. The method involves the addition of an appropriate fuel to a solution containing the metal nitrates in the proper stoichiometry. The ratio of the metal nitrates to the fuel is such that when the solution is dried at around 423 K, the solid residue undergoes flash combustion, giving an ash containing the mixture of oxides in the form of very fine particles (particle size 0.3-0.5 µm). The ash is then given proper heat treatment under the desired atmosphere to obtain the cuprate. The small particle size of the ash facilitates the reaction between the metal oxides due to smaller diffusion distances between the cations. Fuels such as urea [213, 214], glycine [213, 215] and tetraformal triazine (TFTA) [216] are generally employed for synthesizing cuprate superconductors. Ultrafine particles of copper metal can also act as an internal fuel wherein the combustion is initiated by flashing a laser beam for a short time [217]. Some of the cuprate superconductors which have been prepared [213] by this route include  $La_{2-x}Sr_xCuO_4$  ( $T_e = 35$  K),  $YBa_2Cu_3O_7$  $(T_c = 90 \text{ K}), \text{ YBa}_2\text{Cu}_4\text{O}_8 \ (T_c = 80 \text{ K}), \text{ Bi}_2\text{CaSr}_2\text{Cu}_2\text{O}_8$  $(T_c = 85 \text{ K})$ ,  $Pb_2Sr_2Y_{0.5}Ca_{0.5}Cu_3O_8$   $(T_c = 60 \text{ K})$  and  $Nd_{2-x}Ce_xCuO_4$  ( $T_e \sim 30 K$ ).

#### 7. Other methods

In addition to the various synthetic methods discussed hitherto, a few other methods such as spray drying [218-221], freeze drying [186, 222, 223], use of metallic precursors [224, 225] and electrochemical methods

[226, 227] have also been employed for the preparation of cuprate superconductors in bulk form. In spray drying, a solution containing the metallic constituents. usually in the form of nitrates, is sprayed in the form of fine droplets into a hot chamber. The solvent evaporates instantaneously, leaving behind intimate mixture of the reactants which on heating at the desired temperature in a suitable atmosphere yields the cuprate. Some of the superconducting cuprates prepared by this method include  $YBa_2Cu_3O_7$  ( $T_c = 91 \text{ K}$ ) YBa2Cu4O8 [218].  $(T_c = 81 \text{ K})$ [219]  $Bi_{1.6}Pb_{0.4}Sr_2Ca_2Cu_3O_{10}$  ( $T_c = 101 \text{ K}$ ) [220, 221]. In freeze drying, the reactants (in a common solvent) are frozen by immersing in liquid nitrogen. The solvent is removed at low pressures to obtain the initial reactants in fine powder form, and these are then processed at an appropriate temperature. For example, YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub>  $(T_c = 87 \text{ K})$  [186], YBa<sub>2</sub>Cu<sub>4</sub>O<sub>8</sub>  $(T_c = 79 \text{ K})$  [222] and  $Bi_{1.6}Pb_{0.4}Sr_{1.6}Ca_2Cu_3O_r$  ( $T_c = 101 \text{ K}$ ) [223] have been prepared by this method.

Metallic precursors have been used in the preparation of 123 and 247 cuprates [224, 225]. For example, oxidizing an Er-Ba-Cu alloy around 1170 K gives superconducting ErBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> with a T<sub>e</sub> of 87 K [224]. Similarly Yb<sub>2</sub>Ba<sub>4</sub>Cu<sub>8</sub>O<sub>15</sub> has been obtained by heating an alloy composition of YbBa<sub>2</sub>Cu<sub>3</sub> (with 33 wt% of silver) under 1 atm oxygen at 1173 K [225].

Making use of electrochemical oxidation,  $La_2CuO_{4+\delta}$  with a  $T_c$  of 44 K has been prepared at room temperature, which is otherwise possible only by use of high oxygen pressures [226, 227].

#### 8. Oxygen non-stoichiometry

Oxygen stoichiometry plays a crucial role in determining the superconducting properties of many of the cuprates. Thus, stoichiometric La<sub>2</sub>CuO<sub>4</sub> is an insulator, while an oxygen-excess material prepared under high oxygen pressures shows superconductivity with a T<sub>c</sub> of 35 K [15]. The same holds for the next member of the homologous family, La<sub>2-x</sub>Sr<sub>x</sub>CaCu<sub>2</sub>O<sub>6</sub> which is superconducting only when there is an oxygen excess [17]. The excess oxygen donates holes in these two systems. In the case of YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-8</sub>, oxygen can be easily removed giving rise to tetragonal non-superconducting YBa<sub>2</sub>Cu<sub>3</sub>O<sub>6</sub>. The YBa<sub>2</sub>Cu<sub>3</sub>O<sub>6</sub> material can be prepared by heating YBa2Cu3O7 in an argon atmosphere at 973 K for extended periods of time [228]. The variation of  $T_c$  with oxygen stoichiometry,  $\delta$ , is well known [229, 230]. When  $\delta$  reaches 0.5, there is an intergrowth of YBa<sub>2</sub>Cu<sub>3</sub>O<sub>6</sub> and YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> and at this composition, the material shows a  $T_c$  of 45 K. The  $\delta = 0.5$  composition is obtained by quenching  $\delta \simeq 0$  material. heated in a nitrogen atmosphere at 743 K [231]. Similarly, by quenching YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7</sub> at 783 K in air.  $YBa_2Cu_3O_{6,7}$  (showing a  $T_e$  of  $\sim 60$  K) is prepared [231]. The  $T_s$  of 90 K is found only when  $\delta \leq 0.2$ YBa2Cu3O6 is readily oxidized back to YBa2Cu3O7. It may be noted that this oxidation-reduction process in

| Cuprate  | T (approx.) | Methods of synthesis   |
|--|-------------|--|
| La <sub>2_s</sub> Sr <sub>s</sub> (Ba)CuO <sub>4</sub>                                 | 35          | Ceramic*, sol-gel, combustion, coprecipitation   |
| La <sub>2</sub> Ca, Sr,Cu <sub>2</sub> O <sub>6</sub>                                  | 60          | Ceramic (high O <sub>2</sub> pressure)*  |
| La <sub>2</sub> CuO <sub>4+3</sub>   | 40          | Ceramic (high O2 pressure)* alkali-flux, hypobromite*  |
| YBa <sub>2</sub> Cu <sub>3</sub> O <sub>7</sub> <sup>b</sup>                           | 90          | Ceramic (annealing in O <sub>2</sub> )*, sol-get*, coprecipitation* combustion                                     |
| YBa <sub>2</sub> Cu <sub>4</sub> O <sub>6</sub> <sup>b</sup>                           | 80          | Ceramic (high O <sub>2</sub> pressure), ceramic (with Na <sub>2</sub> O <sub>2</sub> )* sol-gel*, coprecipitation* |
| Bl <sub>2</sub> CaSr <sub>2</sub> Cu <sub>2</sub> O <sub>8</sub>                       | 90          | Ceramic (air-quench)* sol-gel*, combustion,<br>melt (glass) route*   |
| Bi <sub>2</sub> Ca <sub>2</sub> Sr <sub>2</sub> Cu <sub>3</sub> O <sub>10</sub>        | 110         | Ceramic*, sol-gel, melt route  |
| TiCaBa,Cu,Oa,  | 90          | Ceramic (sealed Ag/Au tube)*   |
| TICa2Ba2Cu3Oa+4  | 115         | Ceramic (sealed Ag/Au tube)*   |
| Tl <sub>2</sub> Ba <sub>2</sub> CuO <sub>6</sub> c                                     | 90          | Ceramic (sealed Ag/Au tube)*   |
| Tl <sub>2</sub> CaBa <sub>2</sub> Cu <sub>2</sub> O <sub>8</sub>                       | 110         | Ceramic (sealed Ag/Au tube)*   |
| Tl <sub>2</sub> Ca <sub>2</sub> Ba <sub>2</sub> Cu <sub>3</sub> O <sub>10</sub>        | 125         | Ceramic (sealed Ag/Au tube)*   |
| TI <sub>D,5</sub> Pb <sub>D,5</sub> CaSr <sub>2</sub> Cu <sub>2</sub> O <sub>0+4</sub> | - 90        | Ceramic (sealed Ag/Au tube)*   |
| Pb <sub>2</sub> Sr <sub>2</sub> Ca <sub>1,2</sub> Y,Cu <sub>3</sub> O <sub>8</sub>     | 70          | Ceramic (low O <sub>2</sub> partial pressure),* sol-gel* (low O <sub>2</sub> partial pressure)                     |
| Pbo.sCuo.sSr2Yo.sCao.sCu2O7  | 45          | Ceramic (flowing O <sub>2</sub> )*   |
| Nd <sub>2</sub> _Ce_CuO <sub>4</sub>   | 30          | Ceramic (low O <sub>2</sub> partial pressure)*   |
|  | *           | Coprecipitation (low O <sub>2</sub> partial pressure)*   |
| Ca, _,Sr,CuO <sub>2</sub>  | 40-110      | Ceramic (high pressures)*  |
| Sr, Nd, CuO <sub>2</sub>   | 40-110      | Ceramic (high pressures)*  |

\* Recommended methods are indicated by asterisks

Other rare-earth compounds of this type are also prepared by similar methods. Oxygen annealing is done below the orthorhombio-tetragonal transition.

Sr analogues of these compounds with different substitutions at Ca and TI sites are prepared by a similar procedure.

YBa2Cu3O7-6 is of topochemical character. The other analogous rare-earth 123 cuprates also behave in a similar way with respect to the variation of  $\delta$  with  $T_c$ [232].

While YBa2Cu4O8 has high oxygen stability, Y<sub>2</sub>Ba<sub>4</sub>Cu<sub>7</sub>O<sub>15-3</sub> shows a wide range of oxygen stoichiometry  $(0 \le \delta \le 1)$  [233]. The maximum  $T_c$  of 90 K is achieved when  $\delta$  is close to zero, and when  $\delta$  reaches unity the material shows a Te of 30 K; there is no structural phase transition accompanying the variation in oxygen stoichiometry. Usually, both yttrium 124 and 247 cuprates and their rare-earth analogues, prepared by the ceramic method under 1 atm oxygen pressure, show  $\delta$  close to zero.

Bismuth cuprates of the type Bi<sub>2</sub>(Ca, Sr), +1 Cu,O2n+4+8 are best prepared by quenching the samples in air or by annealing in a nitrogen atmosphere at appropriate temperatures [53, 234]. Heating the samples in an oxygen atmosphere is no good, possibly because the extra oxygen may add on to the Bi-O layers. In the case of the lead-doped n=3 member (2223), preparing the samples under low partial pressures of oxygen is found to increase the volume fraction of the superconducting phase [235, 236]. The n = 1member, Bi<sub>2</sub>Sr<sub>2</sub>CuO<sub>6+3</sub> shows metallic behaviour when there is excess oxygen [237]. By annealing in a reducing atmosphere (Ar or N2), the excess oxygen can be removed to induce superconductivity.

Oxygen stoichiometry has a dramatic influence on the superconducting properties of thallium cuprates [94, 108, 109, 238-246]. For example, thallium cuprates of the TlCa<sub>n-1</sub>Ba<sub>2</sub>Cu<sub>n</sub>O<sub>2n+3</sub> family, derivatives of the

TlCa<sub>4-1</sub>Sr<sub>2</sub>Cu<sub>8</sub>O<sub>2n+3</sub> family and Tl<sub>2</sub>Ba<sub>2</sub>CuO<sub>6</sub> often have excess oxygen when prepared in sealed tubes. By annealing these samples in a reducing atmosphere (Ar, dilute H2, N2 or vacuum) at appropriate temperatures, the excess oxygen is removed to induce superconductivity in some cases [108, 109, 238]. Annealing at low oxygen partial pressures or in a reducing atmosphere also increases the To of some of the superconducting thallium cuprates to higher values by decreasing the oxygen content [94, 239-246]. These variations are clearly related to the hole concentration where the number of holes decreases by removing excess oxygen, thereby giving the optimal concentration required for maximal T<sub>e</sub> [247].

In lead cuprates of the Pb2Sr2(Ln, Ca)Cu3O8+1 (2213) type, increasing the oxygen content of the material by annealing in an oxygen atmosphere oxidizes the Pb2+ and Cu1+ without affecting the CuO2 sheets, which governs the superconductivity in this material [248]. Though this system shows a wide range of oxygen stoichiometry (associated with a structural phase transition from orthorhombic to tetragonal symmetry), maximum T<sub>c</sub> is observed for any given composition where in  $\delta$  is close to zero [249]. Samples with  $\delta \simeq 0$  are therefore prepared by annealing in a nitrogen atmosphere containing little oxygen. The lead 1212 cuprates, on the other hand, are best prepared in a flowing. oxygen atmosphere. The samples obtained after the oxygen treatment are often not superconducting since there is an oxygen excess. The samples are quenched in air at around 1073 K in order to achieve superconductivity [250].

Superconducting properties of the electron-doped superconductors,  $Nd_{2-x}Ce_xCuO_{4-x}$ , are sensitive to the oxygen content. The as-prepared samples which are semiconducting have oxygen content greater than four. Samples with oxygen content less than four are obtained by annealing in a reducing atmosphere  $(N_2, Ar)$  or dilute  $H_2$  at around 1173 K. Maintaining the oxygen stoichiometry at less than four is essential for having an oxidation state of Cu less than 2+ in this material [251].

#### 9. Concluding remarks


In the earlier sections we presented details of the preparative methods for the synthesis of various families of cuprate superconductors. In addition, we also examined the advantages and disadvantages of the different methods. Since more than one method of synthesis has been employed for preparing any given cuprate, it becomes necessary to make the right choice of method in any given situation. In order to assist in making such a choice, we have tabulated in table 6 the important preparative methods employed to synthesize some of the representative cuprates, where the recommended methods are also indicated.

#### Acknowledgment

The authors thank the various agencies, expecially the National Superconductivity Research Board, University Grants Commission and the US National Science Foundation for support of the research related to cuprate superconductors.

#### References

- [1] Bednorz J G and Müller K A 1986 Z. Phys. B 64 189
- [2] Sleight A W 1988 Science 242 1519
- [3] Rao C N R (ed) 1991 Chemistry of High Temperature
  Superconductors (Singapore: World Scientific)
- [4] Rao C N R 1991 Phil Trans. R. Soc. A 336 595
- [5] Rao C N R and Gopalakrishnan J 1989 New Directions in Solid State Chemistry (Cambridge: Cambridge University Press)
- [6] Rao C N R 1992 Moter. Sci. Eng. at press
- [7] Uchida S, Takagi H, Kitazawa K and Tanaka S 1987 Japan. J. Appl. Phys. 26 L1
- [8] Cava R J, Vandover R B, Batlogg B and Rictman E A 1987 Phys. Rev. Lett 58 408
- [9] Ganguly P, Mohan Ram R A, Sreedhar K and Rao C N R 1987 Solid State Commun. 62 807
- [10] Tarascon J M, Greene L H, Mckinnon W R, Hull G W and Geballe T H 1987 Science 235 1373
- [11] Wang H et al 1987 Inorg. Chem. 26 1474
- [12] Bhat V, Ganguli A K, Nanjundaswamy K S, Mohan Ram R A, Gopalakrishnan J and Rao C N R 1987 Phase Transitions 10 87
- [13] Kaplan M L and Hauser J J 1988 Mater. Res. Bull. 23
- [14] Demazeau G, Trese F, Plante Th F, Chevalier B, Etorneau J, Michel C, Hervieu M, Raveau B, Lejay P, Sulpice A and Tournier T 1988 Physica C 153-155 824



[16] Zhou J, Sinha S and Goodenough J B 1989 Phys. Rev. B 39 12331

- [17] Cava R J, Batlogg B, Vandover R B, Krajewski J J, Waszczak J V, Flemming R M, Peck W Jr, Rupp L W Jr, Marsh P, James A C W P and Schneemeyer L F 1990 Nature 345 6026
- [18] Kinoshita K, Shibata H and Yamada T 1991 Physica C 176 433
- [19] Okai B 1991 Japan. J. Appl. Phys. 30 L179
- [20] Cava R J, Batlogg B, Vandover R B, Murphy D W, Sunshine S, Siegrist T, Rameika J P, Rietman E A, Zahurak S and Espinosa G P 1987 Phys. Rev. Lett. 58 1676
- [21] Rao C N R, Ganguly P, Raychaudhuri A K, Mohan Ram R A and Sreedhar K 1987 Nature 326 856
- [22] Leskela M, Mueller C H, Truman J K and Holloway P H 1988 Mater. Res. Bull. 23 1469; Hepp A F and Gaier J R 1988 Mater. Res. Bull. 23 693
- [23] Rao C N R 1988 J. Solid State Chem. 74 147
- [24] Clarke D R 1987 Int. J. Mod. Phys. B1 170
- [25] Umarji A M and Nanjundaswamy K S 1987 Pramana-J. Phys. 29 L611
- [26] Tarascon J M, Mckinnon W R, Greene L H, Hull L W and Vogel E M 1987 Phys. Rev. B 36 226
- [27] Alario-Franco M A, Moran-Miguelez E, Saez-Puche R, Garcia-Alvarado F, Amador U, Barabona M, Fernandez F, Perez-Frias M T and Vincent J L 1988 Mater. Res. Bull. 23 313
- [28] Manthiram A, Lee S J and Goodenough J B 1988 J. Solid State Chem. 73 278
- [29] Cava R J, Batlogg B, Flemming R M, Sunshine S A, Ramirez A, Rietman E A, Zahurak S M and Vandover R B 1988 Phys. Rep. B 37 5912
- [30] Somasundaram P, Nanjundaswamy K S, Umarji A M and Rao C N R 1988 Mater. Res. Bull. 23 1139
- [31] Veal B M, Kwok W K, Umezawa A, Crabtree G W, Jorgensen J D, Downey J W, Nowicki L J, Mitchell A W, Paulikas A P and Sowers C H 1987 Appl. Phys. Lett. 51 279
- [32] Tarascon J M, Barboux P, Miceli P F, Greene L H, Hull G W, Eibschutz M and Sunshine S A 1988 Phys. Rev. B 37 7458
- [33] Xu Y, Sabatini R L, Moodenbaugh A R, Zhu Y, Shyu S G, Suenaga M, Dennis K W and McCallum R W 1990 Physica C 169 205
- [34] Karpinski J, Kaldis E, Jilek E, Rusiecki S and Bucher B 1988 Nature 336 660
- [35] Cava R J, Krajewski J J, Peck W F Jr, Batlogg B, Rupp L W Jr, Fleming R M, James A C W P and Marsh P 1989 Nature 338 328
- [36] Pooke D M, Buckley R G, Presland M R and Tallon J L 1990 Phys. Rev. B 41 6616
- [37] Hurng W M, Wu S F and Lee W H 1990 Solid State Commun. 76 647
- [38] Rao C N R, Subbanna G N, Nagarajan R, Ganguli A K, Ganapathi L, Vijayaraghavan R, Bhat S V and Raju A R 1990 J. Solid State Chem. 88 163
- [39] Jin S, O'Bryan, Gallagher P K, Tiefel T H, Cava R J, Fastnacht R A and Kammlott G W 1990 Physica C 165 415
- [40] Adachi S, Adachi H, Setsune K and Wasa K 1991 Physica C 175 523
- [41] Buckley R G, Tallon J L, Pooke D M and Presland M R 1990 Physica C 165 391
- [42] Buckley R G, Pooke D M, Tallon J L, Presland M R, Flower N E, Staines M P, Johnson H L, Meylan M, Williams G V M and Bowden M 1991 Physica C 174 383

[44] Tallon J.L. and Lusk J. 1990 Phys. 67 236

[45] Morris D.E., Nickel J.H., Wei J.Y.T., Mar N.G., Scott J.S., Scheven U.M., Hultgren C.T., Markelz A.G., Post J.E., Heaney P.J., Veblen D.R. and Hazen R.M. 1989 Phys. Rev. B 39 7347

[46] Miyatake T, Gotoh S, Koshizuka N and Tanaka S 1989 Nature 341 41

[47] Wada T, Sakurai T, Suzuki N, Koriyama S, Yamauchi H and Tanaka S 1990 Phys. Rev. B 41 11209

[48] Morris D E, Marathe A P and Sinha A P B 1990 Physica C 169 386

[49] Bordet P, Chaillout C, Chevanas J, Hoveau J L, Marezio M, Karpinski J and Kaldis E 1988 Nature 334 596

[50] Morris D E, Asmar N G, Wei J Y T, Sid R L, Nickel J H, Scott J S and Post J E 1989 Physica C 162-164 955

[51] Michel C, Hervieu M, Borel M M, Grandin A, Deslandes F, Provost J and Raveau B 1987 Z. Phys. B 68 421

[52] Maeda H, Tanaka Y, Fukutomi M and Asano T 1988 Japan. J. Appl. Phys. 27 L209

[53] Rao C N R, Ganapathi L, Vijayaraghavan R, Ranga Rao G, Kumari Murthy and Mohan Ram R A 1988 Physica C 156 827

[54] Sastry P V P S S, Gopalakrishnan I K, Sequeira A, Rajagopal H, Gangadharan K, Phatak G M and Iyer R M 1988 Physica C 156 230

[55] Sastry P V P S S, Yakhmi J V and Iyer R M 1989 Physica C 161 656

[56] Wang Z, Statt B W, Lee M J G, Bagheri S and Rutter J 1991 J. Mater. Res. 6 1160

[57] Torrance J B, Tokura Y, LaPlaca S J, Huang T C, Savoy R J and Nazzal A I 1988 Solid State Commun. 66 703

[58] Tallon J L, Buckley R G, Presland M R, Gilberd P W, Brown I W M, Bowden M and Goguel R 1989 Phase Transitions 19 171

[59] Garcia-Alvarado F, Moran E, Alario-Franco M A, Gonzalez M A, Vinvent J L, Cheetham A K and Chippindale A M 1990 J. Less Common. Metals 164-165 643

[60] Ikeda Y, Ito H, Shimomura S, Oue Y, Inaba K, Hiroi Z and Takano M 1989 Physica C 159 93

[61] Maeda A, Hase M, Tsukada I, Noda K, Takebayashi S and Uchinokura K 1990 Phys. Rev. B 41 6418

[62] Sinclair D C, Irvine J T S and West A R 1992 J. Maier. Chem. 2 579

[63] Agostinelli E, Bohandy J, Green W J, Phillips T E, Kim B F, Adrian F J and Moorjani K 1989 J. Mater. Res. 4 1103

[64] Ganapathi L, Sujata Krishna, Kumari Murthy, Vijayaraghavan R and Rao C N R 1988 Solid State Commun. 67 967; Statt B W, Wang Z, Lee M J G, Yakhmi J V, Decamargo P C, Major J F and Rutter J W 1988 Physica C 156 251

[65] Balachandran U, Shi D, Dos Santos D I, Graham S W, Patel M A, Tani B, Vandervoort K, Claus H and Poeppel R B 1988 Physica C 156 649

[66] Green S M, Jiang C, Mei Y, Luo H L and Politis C 1988 Phys. Rev. B 38 5016

[67] Varma K B R, Rao K J and Rao C N R 1989 Appl. Phys. Lett. 54 69

[68] Komatsu T, Sato R, Hirose C, Matusita K and Yamashita T 1988 Japan. J. Appl. Phys. 27 L2293

[69] Pandey D, Mahesh R, Singh A K, Tiwari V S and Kak S K 1991 Physica C 184 135

[70] Bloom I, Frommelt J M, Hash M C, Lanagan M T,

[71] Gruder C S, Gyo M, Gallagher P K, O'Bryan H M, Johnson Sunshine S, Zahurak S M, Jin S and Sherwood R C 1988 Phys. Rev. B 38 757

[72] Shi F, Rong T S, Zhou S Z, Wu X F, Du J, Shi Z H, Cui C G, Jin R Y, Zhang J L, Ran Q Z and Shi N C 1990 Phys. Rev. B 41 6541

[73] Rao C N R, Mohan Ram R A, Ganapathi L and Vijayaraghavan R 1988 Pramana-J. Phys. 30 L495

[74] Zandbergen H W, Huang Y K, Menken M J V, Li J N, Kadowaki K, Menovsky A A, Van Tendeloo G and Amelinckx S 1988 Nature 332 620

[75] Rao C N R, Vijayaraghavan R, Ganapathi L and Bhat S V 1989 J. Solid State Chem. 79 177; Losch S, Budin H, Eibl O, Hartmann M, Rentschler T, Rygula M, Kemmler-Sack S and Heubener R P 1991 Physica C 177 271

[76] Darriet J, Soethout C J P, Chevalier B and Etourneau J E 1989 Solid State Commun. 69 1093

[77] Manivannan V, Gopalakrishnan J and Rao C N R 1991 Phys. Rev. B 43 8686

[78] Rao C N R, Nagarajan R, Vijayaraghavan R, Vasanthacharya N Y, Kulkarni G U, Ranga Rao G, Umarji A M, Somasundaram P, Subbanna G N, Raju A R, Sood A K and Chandrabhas N 1990 Supercond. Sci. Technol. 3 242

[79] Manthiram A and Goodenough J B 1988 Appl. Phys. Lett. 53 420

[80] Xiang X D, McKernan S, Vareka W A, Zettl A, Corkill J L, Barbee T W III and Cohen M L 1990 Nature 348 145

[81] Tokura Y, Arima T, Takagi H, Uchida S, Ishigaki T, Asano H, Beyers R, Nazzal A I, Laccorre P and Torrance J B 1989 Nature 342 890

[82] Remschnig K, Tarascon J M, Ramesh R, Hull G W and Rogl P 1990 Physica C 170 284

[83] Arima T, Tokura Y, Takagi H, Uchida S, Beyers R and Torrance J B 1990 Physica C 168 79

[84] Sequeira A, Rajagopal H, Ganapathi L, Vijayraghavan R and Rao C N R 1989 Int. J. Mod. Phys. 3 445; Lee P, Gao Y, Sheu H S, Petriček V, Restori R. Coppens P, Darovskikh A, Phillips J C, Sleight A W and Subramanian M A 1989 Science 244 62

[85] Cheetham A K, Chippindale A M, Hibble S J and Woodley C J 1989 Phase Transitions 19 223

[86] Sheng Z Z and Hermann A M 1988 Nature 332 55, 138

[87] Shimakawa Y, Kubo Y, Manoko T. Nakabayashi Y and Igarashi H 1988 Physica C 156 97

[88] Torardi C C, Subramanian M A, Gopalakrishnan J, McCarron E M, Calabrese J C, Morrissey K J, Askew T R, Flippens R B, Chowdhry U, Sleight A W and Cox D E 1988 High Temperature Superconductivity (ed R M Metzger) (New York: Gordon and Breach) p 117

[89] Vijayaraghavan R, Rangavittal N, Kulkarni G U, Grantscharova E, Guru Row T N and Rao C N R 1991 Physica C 179 183

[90] Goretta K C, Chen J G, Chen N, Hash M O and Shi D 1990 Mater. Res. Bull. 25 791

[91] Schilling A, Ott H R and Hulliger F 1989 Physica C 157 144

[92] Rao C N R, Ganguli A K and Vijayaraghavan R 1989 Phys. Rev. B 40 2505; Ganguli A K, Vijayaraghavan R and Rao C N R 1989 Phase Transitions 19 213

[93] Parkin S S P, Lee V Y, Nazzal A I, Savoy R, Huang T C, Gorman G and Beyers R 1988 Phys. Rev. B 38

[94] Martin C, Maignan A, Provost J, Michel C, Hervieu M, Tournier R and Raveau B 1990 Physica C 168 8

- [95] Barry J C, Iqbal Z, Ramakrishna B L, Sharma R, Eckhardt H and Reidinger F 1989 J. Appl. Phys. 65
- [96] Gopalakrishnan I K, Sastry P V P S S, Gangadharan K, Phatak G M, Yakhmi J V and Iyer R M 1988 Appl. Phys. Lett. 53 414

[97] Li S and Greenblatt M 1989 Physica C 157 365

[98] Ganguli A K, Nanjundaswamy K S, Subbanna G N, Rajumon M K, Sarma D D and Rao C N R 1988 Mod. Phys. Lett. B 2 1169

[99] Sleight A W 1991 Phys. Today 44 24

- [100] Parkin S S P, Lee V Y, Engler E M, Nazzal A I, Huang T C, Gorman G, Savoy R and Beyers R 1988 Phys. Rev. Lett. 60 2539
- [101] Vijayaraghavan R. Gopalakrishnan J and Rao C N R 1992 J. Mater. Chem. 2 237
- [102] Suigse R, Herbayashi M, Trerada N, Jo M, Shimomura T and Ihara H 1988 Japan. J. Appl. Phys. 27 1709
- [103] Suigse R, Herbayashi M, Trerada N, Jo M, Shimomura T and Ihara H 1989 Physica C 157 131
- [104] Ganguli A K, Nanjundaswamy K S and Rao C N R
- 1988 Physica C 156 788
  [105] Subramanian M A, Torardi C C, Gopalakrishnan J, Gai P L, Calabrese J C, Askew T R, Flippen R B and Sleight A W 1988 Science 242 249
- [106] Subramanian M.A., Gai P.L. and Sleight A.W. 1990 Mater. Res. Bull. 25 101
- [107] Pan M H and Greenblatt M 1991 Physica C 176 80
- [108] Pan M H and Greenblatt M 1991 Physica C 184 235
- [109] Ganguli A K, Manivannan V, Sood A K and Rao CNR 1989 Appl. Phys. Lett. 55 2664
- [110] Manivannan V, Ganguli A K, Subbanna G N and Rao CNR 1990 Solid State Commun. 74 87
- [111] Manako T, Shimakawa Y, Kubo Y, Satoh T and Igarashi H 1989 Physica C 158 143
- [112] Martin C, Bourgault D, Hervieu M, Michel C, Provost J and Raveau B 1989 Mod. Phys. Lett. B3 993
- [113] Vijayaraghavan R 1992 PhD Thesis Indian Institute of Science
- [114] Liu R S, Hervieu M, Michel C, Maignan A, Martin C, Raveau B and Edwards P P 1992 Physica C 197
- [115] Torardi C C, Subramanian M A, Calabrese J C, Gopalakrishnan J, Morrissey K J, Askew T R, Flippen R B, Chowdhry U and Sleight A W 1988 Science 240 631

[116] Cava R J et al 1988 Nature 336 211

- [117] Koike Y, Masuzawa M, Noji T, Sunagawa H, Kawabe H, Kobayashi N and Saito Y 1990 Physica C 170 130
- [118] Subramanian M A, Gopalakrishnan J, Torardi C C, Gai P L, Boyes E D, Askew T R, Flippen R B, Farneth W E and Sleight A W 1989 Physica C 157
- [119] Kadowaki K, Menken M J V and Moleman A C 1989 Physica C 159 165
- [120] Ramprasad, Soni N C, Adhikary K, Malik S K and Tomy C V 1990 Solid State Commun. 76 667
- [121] Retoux R, Michel C, Hervieu M and Raveau B 1989 Mod. Phys. Lett. B3 591
- [122] Zandbergen H W, Fu W T, Van Ruitenbeck J M and Amelinckx S 1989 Physica C 159 81
- [123] Adachi S, Setsune K and Wasa K 1990 Japan. J. Appl. Phys. 29 L890
- [124] Maeda T, Sakuyama K, Koriyama S, Yamauchi H and Tanaka S 1991 Phys. Rev. B 43 7866
- [125] Rouillon T, Provost J, Hervieu M, Groult D, Michel C and Raveau B 1989 Physica C 159 201
- [126] Rouillon T, Maignan A, Hervieu M, Michel C, Groult D and Raveau B 1990 Physica C 171 7
- [127] Liu R S, Wu S F, Gameson I, Edwards P P, Maignan

- A, Rouillon T, Groult D and Raveau B 1991 J. Solid State Chem. 93 276
- [128] Mohan Ram R A and Clearfield A 1991 Chem. Mater.
- [129] Maeda T, Sakuyama K, Koriyama S, Ichinose A, Yamauchi H and Tanaka S 1990 Physica C 169 133
- [130] Tang X X, Morris D E and Sinha A P B 1991 Phys. Rev. B 43 7936
- [131] Liu H B and Morris D E 1991 Phys. Rev. B 44 5369
- [132] Tokura Y, Takagi H and Uchida S 1989 Nature 337
- [133] Markert J T and Maple M B 1989 Salid State Commun. 70 145
- [134] Markert J T, Early E A, Bjornholm T, Ghanaty S, Lee B W, Neumier J J, Price R D, Seaman C L and Maple M B 1989 Physica C 159 178
- [135] Lopez-Morales M E, Savoy R J and Grant P M 1990 J. Mater. Res. 5 2041
- [136] James A C W P, Zahurak S M and Murphy D W 1989 Nature 338 240
- [137] Felner I, Yaron U, Yeshurun Y, Yacoby E R and Wolfus Y 1989 Phys. Rev. B 40 11366
- [138] Ayoub N Y, Almasan C C, Early E A, Markert J T, Seaman C L and Maple M B 1990 Physica C 170
- [139] Takano M, Azuma M, Hiroi Z, Bando Y and Takeda Y 1991 Physica C 176 441
- [140] Takano M, Hiroi Z, Azuma M and Takeda Y 1992 Chemistry of High Temperature Superconductors (cd CNR Rao) (Singapore: World Scientific) p 243
- [141] Smith M G, Manthiram A, Zhou J, Goodenough J B and Markert J T 1991 Nature 351 549
- [142] Azuma M, Hiroi Z, Takano M, Bando Y and Takeda Y 1992 Nature 356 775
- [143] Capone D W, Hinks D G, Jorgensen J D and Zhang Z K 1987 Appl. Phys. Lett. 50 543
- [144] Bednorz J G, Takashige M and Müller K A 1987 Mater. Res. Bull. 22 819
- [145] Jorgensen J D, Schuttler H B, Hinks D G, Capone D W. Zhang K. Brodsky M B and Scalapino D 1987 Phys. Rev. Lett. 58 1024
- [146] Otamin' J C and Anderson A 1990 J. Mater. Res. 5 1388
- [147] Panayappan R M, Guy J T, Binstead R, Toysneau V L and Cooper J C 1988 Phys. Rev. B 37 3727
- [148] McIntyre P.C. Cima M J. Man Fai Ng. Chiu R C and Rhine W E 1990 J. Mater. Res. 5 2771
- [149] Manthiram A and Goodenough J B 1987 Nature 329 701
- [150] Wang X Z, Henry M, Livage J and Rosenmann I 1987 Solid State Commun. 64 881
- [151] Clark R J, Harrison L L, Skirius S A and Wallace W J 1990 Mol. Cryst. Liq. Cryst. 184 377
- [152] Vos A, Carleer R, Mullens J, Yperman J, Vanhees J and Van Poucke L. C 1991 Eur. J. Solid State Inorg. Chem. 28 657
- [153] Vilminot S, Hadigui S El and Desory A 1988 Mater. Res. Bull. 23 521
- [154] Pramanik P, Biswas S, Singh C, Bhattacharya D, Dey T K, Sen D, Ghatak S K and Chopra K L 1988 Mater. Res. Bull. 23 1693
- [155] Kellner K, Wang X Z, Gritzner G and Bauvale D 1991 Physica C 173 208
- [156] Liu R S, Chang C T and Wu PT 1989 Inorg. Chem. 28 154
- [157] Horowitz H S, Mclain S J, Sleight A W, Druliner J D. Gai P L, Van Kavelaar M J, Wagner J L, Biggs B D and Poon S J 1989 Science 243 66
- [158] Kini A M, Geiser U, Kao H C I, Carlson D K, Wang H H, Monaghan M R and Williams J M 1987 Inorg. Chem. 26 1834

[160] Ho J.S. Liu R S. Chang C T and I rds P P 1991

[161] Chen W L, Huang Y, Wu M K, Wang M J, Chen D H, Sheen S R and Chang C T 1991 Physica C 185-189 483

[162] Guptasarma P, Palkar V R and Multani M R 1991 Solid State Commun. 77 769

[163] Liu R S, Ho J S, Chang C T and Edwards P P 1991 J. Solid State Chem. 92 247

[164] Das Santos D I, Balachandran U, Guttschow R A and Poeppel R B 1990 J. Non-Cryst. Solids 121 441

[165] Zhang Y, Fang Z, Muhammed M, Rao K V, Skumryev V, Medeliu H and Costa J L 1989 Physica C 157 108

[166] Marbach G, Stotz S, Klee M and Devries J W C 1989 Physica C 161 111

[167] Takano M, Takada J, Oda K, Kitaguchi H, Miura Y, Ikeda Y, Tomi Y and Mazaki H 1988 Japan. J. Appl. Phys. 27 L1041

[168] Chen F H, Hoo K S and Tseng T Y 1990 J. Mater. Sci. 25 3338

[169] Hagberg J, Vusimaki A, Levoska J and Leppavuori S 1989 Physica C 160 369

[170] Gritzner G and Bernhard K 1991 Physica C 181 201

[171] Chiang C, Shie C Y, Huang Y T, Lee W H and Wu P T 1990 Physica C 170 383

[172] Chen D Y, Shei C Y, Sheen S R and Chang C T 1991 Japan J. Appl. Phys. 30 1198

[173] Shei C Y, Liu R S, Chang C T and Wu P T 1990 Inorg. Chem. 29 3117

[174] Bernhard K, Gritzner G, Wang X Z and Bauerle D 1990 J. Solid State Chem. 86 293

[175] Schrodt D J et al 1988 Solid State Commun. 67 871

[176] Borik M, Chernikov M, Dubov I, Osiko V, Veselago V. Yakowets Y and Stepankin V 1992 Supercond. Sci. Technol. 5 151

[177] Bernhard K and Gritzner G 1992 Physica C 196 259

[178] Kordas G, Wu K, Brahme U S, Friedmann T A and Ginsberg D M 1987 Mater. Lett. 5 417

[179] Shibata S, Kitagawa T, Okazaki H, Kimura T and Murakami T 1988 Japan J. Appl. Phys. 27 L53

[180] Kordas G, Moore G A, Jorgensen J D, Rotella F. Hitterman R L, Volin K J and Faber J 1991 J. Mater. Chem. 1 175

[181] Katayama S and Sekine M 1990 J. Mater. Res. 5 683

[182] Murakami H, Yaegashi S, Nishino J, Shiohara Y and Tanaka S 1990 Japan. J. Appl. Phys. 29 2715

[183] Catania P, Hovnanian N, Cot L, Pham Thi M, Kormann R and Ganne J P 1990 Mater. Res. Bull. 25 631

[184] Bowmer T N and Shokoohi F K 1991 J. Mater. Res. 6 670

[185] Nagano M and Greenblatt M 1988 Solid State Commun. 67 595

[186] Barboux P, Tarascon J M, Greene L H, Hull G W and Bagley B G 1988 J. Appl. Phys. 63 2725

[187] Fujiki M, Hikita M and Sukegawa K 1987 Japan. J. Appl. Phys. 26 L1159

[188] Karis T E and Economy J 1991 J. Mater. Res. 6 1623 [189] Chu C T and Dunn B 1987 J. Am. Ceram. Soc. 70 C375

[190] Blank D.H.A., Kruidhof H.K. and Flokstra J. 1988 J. Phys. D.: Appl. Phys. 21 226

[191] Sanjines R, Ravindranathan Thampi K and Kiwi J 1988 J. Am. Ceram. Soc. 71 512

[192] Yang Y M, Out P, Zhao B R, Zhao Y Y, Li L, Ran Q Z and Jin R Y 1989 J. Appl. Phys. 66 312

[193] Liu R S, Wang W N, Chang C T and Wu P T 1989 Japan. J. Appl. Phys. 28 L2155

[194] Lee H K, Kim D and Sucks S 1 1989 J. Appl. Phys. 65 2563 [196] Katayama S and the M 1991 J. Mater. Res. 6 1629; 1991 J. Mater. Them. 1 1031

[197] Zhang S C, Messing G L, Huebner W and Coleman M M 1990 J. Mater. Res. 5 1806

[198] Sakka S, Kozuka H and Zhuang H 1990 Mol. Cryst. Liq. Cryst. 184 359

[199] Koriyama S, Ikemachi T, Kawano T, Yamauchi H and Tanaka S 1991 Physica C 183-189 519

[200] Murakami H, Yaegashi Y, Nishino J, Shiohara Y and Tanaka S 1990 Japan J. Appl. Phys. 29 L445

[201] Liu R S, Jones R, Bennett M J and Edwards P P 1990 Appl. Phys. Lett. 57 920

[202] Koyama K, Junod A, Graf T, Triscone G and Muller J 1991 Physica C 185-189 461

[203] Kakihana M, Kall M, Borjesson L, Mazaki H, Yasuoka H, Berastegui P, Erikkson S and Johansson L G 1991 Physica C 173 377

[204] Dhalle M, Van Haesendonck C, Bruynseraede Y, Kwarciak J and Van der Biest O 1990 J. Less Common Metals 164-165 663

[205] Tanaka K, Nozue A and Kamiya K 1990 J. Mater. Sci. 25 3551

[206] Masuda Y, Ogawa R, Kawate Y, Tateishi T and Hara N 1992 J. Mater. Res. 7 292

[207] Mahesh R, Nagarajan R and Rao C N R 1992 J. Solid State Chem. 96 2

[208] Ham W. K., Holland G. F and Stacy A. M. 1988 J. Am. Chem. Soc. 110 5214

[209] Subramanian M A, Gopalakrishnan J, Torardi C C, Askew T R, Flippen R B, Sleight A W, Liu J J and Poon J J 1988 Science 240 495

[210] Rudolf P and Schöllhorn R 1992 JCS Chem. Commun. 1158

[211] Coppa N, Nichols D H, Schwegler J W, Crow J E, Myer G H and Salomon R E 1989 J. Mater. Res. 4 1307; Coppa N, Kebede A, Schwegler J W, Perez I, Salomon R E, Myer G H and Crow J E 1990 J. Mater. Res. 5 2755

[212] Merzhanov A G and Borovinskaya I P 1972 Dokl. Acad. Nauk. 204 366

[213] Mahesh R, Vikram A Pavate, Om Prakash and Rao C N R 1992 Supercond. Sci. Technol 5 174

[214] Varma H, Warrier K G and Damodaran A D 1990 J. Am. Ceram. Soc. 73 3103

[215] Pederson L R, Maupin G D, Weber W J, McReady D J and Stephens R W 1991 Mater. Lett. 10:437

[216] Sundar Manoharan S, Prasad V, Subramanyam S V and Patil K C 1992 Physica C 190 225
 [217] Lepart J P and Varma A 1991 Physica C 184 220

[218] Kourtakis K, Robbins M and Gallagher P K 1989

J. Solid State Chem. 82 290

 [219] Kourtakis K, Robbins M, Gallagher P K and Tiefel T 1989 J. Mater. Res. 4 1289
 [220] Tomizawa T, Matsunaga H, Fujishiro M and

Kakegawa H 1990 J. Solid State Chem. 89 212
[221] Tripathi R B and Johnson D W Jr 1991 J. Am. Ceram.
Soc. 74 247

[222] Horn J, Borner H, Semmelhack H C, Lippold B, Hermann J, Wurlitz M, Krotzsch M, Boehnke U, Schlenkrich F and Frenzel Ch 1991 Solid State Commun. 79 483

[223] Song K H, Liu H K, Dou S and Sorrell C C 1990 J. Am. Ceram. Soc. 73 1771

[224] Matsuzaki K, Inone A, Kimura H, Aoki K and Masumoto T 1987 Japan. J. Appl. Phys. 26 L:1310

[225] Kogure T, Kontra R, Yurek G J and Vander Sande J B 1988 Physica C 156 45

[226] Grenier J C, Wattiaux A, Lagueyte N, Park J C, Marquestaut E, Etourneau J and Pouchard M 1991 Physica C 173 139

# This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

| ☐ BLACK BORDERS   |
|---|
| ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES                 |
| ☐ FADED TEXT OR DRAWING                                 |
| ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING                  |
| ☐ SKEWED/SLANTED IMAGES                                 |
| ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS                  |
| ☐ GRAY SCALE DOCUMENTS                                  |
| LINES OR MARKS ON ORIGINAL DOCUMENT                     |
| ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY |
| OTHER.  |

## IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.